

Test tube shaker

TTS 2

- ☒ **Universal shaker for test tubes and small vessels**
- ☒ **Continuous operation or automatic mode of operation by pressure on the top attachment**
- ☒ **A large selection of attachments allows for an extensive range of applications**

| | |
|---|-------------------|
| Shaking motion: | orbital |
| Shaking orbit: | Ø 4,5 mm |
| Perm. agitation weight (with attachment): | 0,5 kg |
| Motor rating input/output: | 30 / 23 W |
| Permissible ON-time: | 100 % |
| Speed range (infinitely adjustable): | 0 - 2.500 rpm |
| Speed display: | scale / analog |
| Dimensions (W x D x H): | 115 x 225 x 60 mm |
| Weight: | 3,5 kg |
| Protection class acc. to DIN EN 60529: | IP 21 |



MS 1.34 Id-Nr. L001830

Test tube insert MS 1.34

No pre-drilled holes. Any number of holes may be drilled.



MS 1.33 Id-Nr. L001860

Test tube insert MS 1.33

4 holes, Ø 15 mm



MS 1.32 Id-Nr. L001850

Test tube insert MS 1.32

6 holes, Ø 10 mm



MS 1.31 Id-Nr. L001840

Test tube insert MS 1.31

14 holes, Ø 8 mm

سوماتكو
SOMATCO
www.somatco.com



Connect With Us

