

BA-88A

Semi-Auto Chemistry Analyzer

Specifications

TESTING ITEM

ALT, AST, ALP, ACP, GGT, α -HBDH, LDH, CK, AMY, TG, TC, HDL-c, LDL-c, UA, UREA, Cr, Glu, TP, Alb, T-Bil, D-Bil, TBA, NH_4^+ , HCO_3^- , Ca, Mg, Cl, Na, K, apoA1, apoB, Lp(a), C3, C4, IgG, IgA, IgM, HbA1c, Alcohol, Amphetamines, Barbiturates, Benzodiazepine etc.

ANALYSIS METHOD

Endpoint, with or without reagent blank
Endpoint, with sample blank and reagent blank
Kinetics, with or without reagent blank
Two point Kinetics / Fixed time, with or without reagent blank
Absorbance
Turbidimetry
Linear and non-linear calibration

LIGHT SOURCE

Tungsten-halogen lamp 6V/10W

WAVELENGTH RANGE

Automatic by 8-position filter wheel
8 standard filters: 340nm, 405nm, 450nm, 510nm, 546nm, 578nm, 630nm and 670nm.
Bandwidth < 8nm
Stray light: <0.1% @ 340nm

PHOTOMETRIC RANGE

0~3.5 ABS
Stability: <0.005A/20min @340nm

FLOWCELL

Stainless steel with quartz window
Measuring volume: 32 μ l
Optical path: 10mm
Aspiration volume programmable: 200-9000 μ l

INPUT

Touch screen with touch pen and popup keypad
Mouse or Keyboard via USB

TEMPERATURE CONTROL

By means of Peltier elements
Room temperature, 25 $^{\circ}$ C, 30 $^{\circ}$ C or 37 $^{\circ}$ C

STORAGE

No less than 3000 sample results
No less than 1000 QC results

PRINTER

Built-in thermal printer
Supporting HP series

INTERFACE

RS232 serial port supporting data transmission
USB port (2.0), for keyboard, mouse, printer

OPERATING ENVIRONMENT

Temperature: 15 $^{\circ}$ C -30 $^{\circ}$ C
Humidity: 35%-85%, no condensation

POWER REQUIREMENT

Wide power supply: AC 100-240V~, 50/60Hz

DIMENSION

430mm \times 360mm \times 170mm (L \times W \times H)

WEIGHT

6.8kg



MINDRAY™

Mindray Building, Keji 12th Road South, High-tech Industrial Park,
Nanshan, Shenzhen 518057, P. R. China

Tel: +86 755 26582492, 26582888 Fax: +86 755 26582680

E-mail: intl-market@mindray.com

Website: www.mindray.com



DISTRIBUTOR: