



Profilo antibordamento e parete antispruzzo



C 618/C 619



Suspended electronic hand-washing unit in 1.5 mm-thick AISI 316 stainless steel with panelling under basin. The basculating unit allows easy accessibility to all components for maintenance and inspection. Particularly suitable for operating departments of hospitals and clinics. Tank depth: 35 cm. The outer edge of the tank is overflow-

proof. The front part has rounded inside edges and an inclination of 50° to prevent water from spraying outside. The drain has been obtained directly in the base of the tank to avoid any spreading of bacteria. Equipped with 220/18Vac safety transformer approved by IMQ, stopcocks with check valves and inspectionable filters, U-trap,

two flexible connecting pipes. CE certified. The hand-washing units are available in different versions:

- with one tap (C619)
- with two taps (C618)
- custom-made (maximum length of the tank: 240 cm) with different combinations of taps, soap dispensers and thermostatic mixers.

- Operating pressure: 1÷10 bar
- Water flow at 3 bar: 8 l/min
- Supply: 220/18Vac 10VA transformer Class II IP40



VERSIONS

with thermostatic mixer	C618MXSRT	2 taps 1 soap dispenser 1 miscelatore termostatico
for cold or premixed water	C618SRT	2 taps 1 soap dispenser
	C618RT	2 taps

VERSIONS


with thermostatic mixer	C619MXSRT	1 tap 1 soap dispenser 1 miscelatore termostatico
for cold or premixed water	C619SRT	1 tap 1 soap dispenser
	C619RT	1 tap



C 609

Suspended electronic hand-washing unit and sterilizer (technical features SZ101) in one single unit in AISI 304 stainless steel with panelling under basin. The basculating unit allows easy accessibility to all components for maintenance and inspection. Rectangular tank of the hand-washing unit with rounded edges, without overflow. Electronic tap endowed with an incorporated automatic shutoff device. (interruption of the water flow after 60" of continuous functioning). Equipped with 220/18Vac safety transformer approved by IMQ, stopcocks with check valves and inspectionable filters, U-trap for hand-washing unit, two flexible connecting pipes. CE certified.

- Operating pressure: 1 – 10 bar
- Water flow at 3 bar: 8 l/min
- Operating Voltage: Sterilizer 220V tap 220/18Vca 10VA II class IP40
- Power of the sterilizer: 2300 watt



VERSIONS


con miscelatore termostatico	C609MXSRT	1 tap 1 soap dispenser 1 miscelatore termostatico
For cold or premixed water	C609SRT	1 tap 1 soap dispenser
	C609RT	1 tap

SZ 101

Suspended knives sterilizer with tank and panelling under basin in AISI 304 stainless steel. The cylindrical tank (max. cap. 7.5 l) has a concave lower part and consists of one single-block unit without welding. Fitted with a removable central drain of the overflow in stainless steel. Heating element in stainless steel powered by 220V/2300W and thermostat (adjusted at 85° but adjustable from 0° to 100°) placed outside the tank. Removable knives-holder in nylon. Manual tap for filling up of the tank. The hydraulic parts of the tap are in solid brass while all parts in contact with water are perfectly smooth. Equipped with stopcock

with check valve and inspectionable filter, flexible connecting pipe. CE certified.

- Operating Voltage: 220V



VERSIONS

SZ101	Max temp 85°
--------------	--------------