

Rotary Microtome CUT 6062

Precise full automation in modular design



Microtomes

CUT 4062

CUT 5062

► CUT 6062

MTR

Cryostats

Paraffin

Embedding Centers

Tissue processors

Stainers

Cover slipper

Knife sharpener

Floating bath

Slide warmer

Rotary Microtome CUT 6062

Precise full automation in modular design



Standard unit for paraffin sections and research-, plastic- and industrial applications. The fully motorised unit offers an even greater comfort than manual and semi-automatic microtomes whilst retaining all essential features of this series.

Additional features are:

- ▶ *Motor drive*
- ▶ *Footswitch*
- ▶ *Emergency stop*
- ▶ *Operating pad for motorised cutting*
- ▶ *Operating pad for motorised advance / return*
- ▶ *Individual or series cutting*
- ▶ *Advance automatic in 2 speeds*
- ▶ *Specimen final position can be selected, top or bottom*
- ▶ *Specimen size up to 50 x 50 mm with standard object clamp or standard cassette size for universal cassette clamp*
- ▶ *Motorized cutting steplessly adjustable*
- ▶ *Speed for cutting and returning specimen can be adjusted seperately*
- ▶ *Universal power unit 100 – 240 V, 50/60 Hz*
- ▶ *The equipment is supplied completely useable including:*
 - *Object orientation unit alternatively fixed*
 - *Universal cassette clamp alternatively standard object clamp*
 - *Knife holder base with disposable blade holder low profile or high profile alternatively standard knife holder*
 - *Section waste tray*



The operating pad for advance / retraction, slow motion, cutting thickness adjustment and trimming



CUT 4062 – manual model



Technical Data

Range of thickness	0,5 µm – 100 µm
Increments	0,5 µm from 0,5 µm – 2,0 µm 1,0 µm from 2,0 µm – 10 µm 2,0 µm from 10 µm – 50 µm 5,0 µm from 50 µm – 100 µm
Horizontal specimen advance	28 mm
Vertical stroke	60 mm
Specimen orientation	XY-Axes: 8°, Z-Axes: 360°
Cutting speed	steplessly adjustable from 3 – 300 mm/sec
Advance for trimming	adjustable from 0 – 300 µm, free programmable

Weight and Dimensions

	Depth x Width x Height	
Dimensions (in mm)	495 x 400 x 290	
Dimensions packed (in mm)	650 x 550 x 480	
Weight net	29 kg	
Weight packed	41 kg	
Electrical parameters	Art.-No. 1080001	230 V / 50 Hz
	Art.-No. 1081001	230 V / 60 Hz
	Art.-No. 1082001	115 V / 60 Hz
	Art.-No. 1083001	100 V / 50 Hz
	Art.-No. 1084001	100 V / 60 Hz

Please ask for other units for Histopathology and consumables as well as laminar flow equipment.