

Manufacturer Specifications - EBA 12R, Hettich

MODEL	EBA 12R
OTHER AVAILABLE	
POWER CONSUMPTION (TEMPERATURE)	420W
REVOLUTIONS	
Max. speed (REVOLUTIONS)	15000
Max. force (REVOLUTIONS)	20879
Settings (REVOLUTIONS)	10rpm increments
ROTOR RADIUS, cm (REVOLUTIONS)	8.3
POWER NEEDED, VAC (ENERGY)	115/230
COVER LOCK (ACCELERATION)	Yes
WARNING SIGNALS (REVOLUTIONS)	Imbalance, lid open, electronics, error codes
DIMENSIONS (HXWXD) CM, (IN) (DISPLAY)	29.5x 30 x 61.5
WEIGHT, kg (lb) (DISPLAY)	30(66.1)
ROTORS	
TIMER	
Range, min	Up to 120 minutes ¹⁻⁹⁹ , continuous
Increments (TIMING DEVICE)	1min
BRAKING TIME, sec (TIMING DEVICE)	20
SOUND LEVEL, DB	45-58
CAPACITY	
No. 75 mm capillary tubes (40-60 mL) (No. 75 mm capillary)	24
OTHER ATTRIBUTES (Interference compensation)	Brushless; rotor
MARKETING REGION (Interference compensation)	Worldwide



You may also be interested in the following Manufacturer Specifications:

- [Haematokrit 210 Manufacturer Specification](#)
- [EBA 21 Manufacturer Specification](#)
- [Haematokrit 20 Manufacturer Specification](#)

Disclaimer

Information on this page may be partial or incomplete and may contain mistakes or inaccurate information. MedWOW disclaims any obligation, responsibility or liability which concerns or relates to any information on this page.

Close

