

Characteristics



Structure	White or Stainless steel 18/10 int.+ext.
Insulation thickness	60 (polyur. mm)
Doors number	1
Door type	Glass
Refrigeration type	Ventilated
Refrigerant type	R134A
Temperature range	+4°
Temperature control/adjustment	ECT-F Control® : with Hi/Low Temp. alarm, door ajar, ON/OFF w/password
Defrosting type	Auto
Voltage	230V/1/50HZ 220V/1/60HZ
Capacity (LT)	700
Safety key locking	standard fitted
Internal lighting	standard fitted
DMLP Digital Monitor (Alarm System)	standard fitted
Drawers nr.	7
Storage capacity (blood bags nr., 450 ml)	336
Width (cm)	72
Depth (cm)	83
Height (cm)	205
Net weight (Kg)	191
Equipment in accordance with	Directive 93/42/EEC annex V, article 3 and following modifications

Automatic water evaporation
 Probe for product simulation
 Ext. terminal board for RS485/dry contacts
 Available also with fully insulated door

Cooling unit of monoblock type with compact evaporator ceiling mounted for a bigger internal capacity of the refrigerated cabinet

Accessories

- DMLP Printer
- Drawer perspex front (H=83 mm)
- Kit of castors with brakes
- PT100 probe
- WEB LIGHT SERVER (Ethernet + GSM)
- GSM Communicator CF2008 module
- DMLP Remote panel
- DMLP PT100 Extension module + nr.1 PT100 probe + 4-20mA output
- Voltage 115V



At any time, the manufacturer may bring modifications to the model above described, for technical or commercial reasons. The picture does not necessary shows the product in the standard version.