

Hot Plates

LARGEST ALUMINUM TOP

Thermolyne

Type HPA2240 and HPA22300



LARGEST SURFACE FOR LARGEST LOADS!

- — Largest heating surface
- — Excellent temperature control
- — Up to 40 lb. (18.2 kg) loads



PRODUCT DESCRIPTION

- Aluminum top plate outperforms other materials; provides superior temperature uniformity and stability.
 - Uniformity at 100°C (212°F):**
 - HPA2235M $\pm 4.0^{\circ}\text{C}$ (7.2°F)
 - HPA2245M $\pm 10.0^{\circ}\text{C}$ (18.0°F)
 - Stability at 100°C (212°F):**
 - HPA2235M $\pm 3.0^{\circ}\text{C}$ (5.4°F)
 - HPA2245M $\pm 3.5^{\circ}\text{C}$ (6.3°F)
- Thermostatic temperature control senses and maintains hot plate temperature, provides excellent stability.
- Solid state relay and electronically controlled circuitry in 12" x 24" (30.5 x 60.9 cm) hot plate ensures safety and reliability for your high wattage applications.
- Embedded heating elements transfer heat evenly to top plate; provides uniform temperature.
- Cycle light indicates when power is being supplied to heating element.
- Stainless steel case provides optimal strength for heavy loads.
- 12" x 24" (30.5 x 60.9 cm) hot plate case is painted with epoxy paint for increased chemical resistance in corrosive environments.
- High wattage input is ideal for sizable heating tasks.
- Large 12" x 12" (30.5 x 30.5 cm) and 12" x 24" (30.5 x 60.9 cm) top plate surfaces accommodate up to 40 lb. (18.2 kg) loads.
- Recommended for use with glass vessels only.

APPLICATION

- Acid/Base digestions - trace metal analysis, etc.
- Sample drying.
- General reagent heating.
- Heating TLC plates.
- Evaporations.

48 Hour or Sooner
Express Shipping
Guaranteed!*



PRODUCT SPECIFICATIONS

Type	Heating Surface Inches (cm)		Overall Dimensions Inches (cm)			Shipping Weight Lb. (kg)
	W	D	W	H	D	
12" x 12" (30.5 cm x 30.5 cm) Heating Surface						
HP2200	12 (30.5)	12 (30.5)	12 (30.5)	6.13 (15.6)	13 (33)	21 (9.5)
12" x 24" (30.5 cm x 60.9 cm) Heating Surface						
HP2200	24 (60.9)	12 (30.5)	24 (60.9)	6.25 (15.9)	13.75 (34.9)	43 (19.5)

12" X 24" (30.5 cm x 60.9 cm) top plate models not supplied with cord and plug due to high-wattage consumption requirements; must be connected through electrical conduit fittings.

ORDERING INFORMATION

Model #	Electrical (50/60 Hertz)			Operating Temp Range		US List Price
	Volts	Amps	Watts	°C	°F	
HPA2235M*	120	13.3	1600	38-371	100-700	
HPA2238M	208	7.7	1600	38-371	100-700	
HPA2230M*	240	6.7	1600	38-371	100-700	
HPA2230M-26	240	6.7	1600	38-371	100-700	
HPA2245M*	120	26.6	3200	38-371	100-700	
HPA2248M	208	15.4	3200	38-371	100-700	
HPA2240M*	240	13.3	3200	38-371	100-700	

* UL and CSA listed, -26 Models Supplied with European cord set.

سوماتكو
SOMATCO
www.somatco.com



Connect With Us

