OMEGA®
A SIGN OF QUALITY PRODUCT

PANEL METERS MOVING COIL D.C. (FITTED ON BAKELITE STAND)

OMEGA TYPE MO-65

GENERAL FEATURES

01 Sturdy Movement.
02 Accuracy : ± 1.5% of F.S.D.
03 Linearity : Better than 1% on printed dials.
04 Basis sensitivities : 10 µA to 5 mA.
05 Overload capacity : 10 times F.S.D.
06 Size : 65mm round flush
07 Pivot : Jewel construction.
08 Higher momentary overload can be withstood.
09 Phenolic moduled case with glass front to avoid static charge effect
10 Knife edge pointer for accurate readings.
11 Fitted on bakelite stand with two lock type terminals

OMEGA®
A SIGN OF QUALITY PRODUCT

STANDARD RANGES

01 MILLIAMMETERS : 0-1, 1.5, 3, 5, 6,10, 15,20,25,30, 40, 50, 60, 100, 150,200, 250, 300, 500 & 750mA.
02 AMMETERS : 0-1, 1.5, 2, 2.5, 3, 5, 6, 10, 15, 20, 25, & 30Amp.
03 MILLIVOLTMETERS : 0-100, 150, 200, 250, 300, 500 750mV.
04 VOLTMETERS : 0-1, 1.5, 2, 2.5, 3, 5, 6, 10, 15, 20, 25, 30, 40, 50, 60, 75, 100, 125, 150, 200, 250, 300, 500 & 600V (1000 Ohms/Volt)
05 GALVANOMETERS : 30-0-30 & 50-0-50 Sensitivity of 20µA/div,
06 GALVANOMETERS : 30-0-30 G Push Button Controlled TYPE MO-65PB
07 Weight : 0.5 Kg. (Approx)

سوماتكو
SOMATCO
www.somatco.com
Connect With Us