

MW-12

Microplate Washer

NEW



- Flexible and ease-of-use
- 8-way and 12-way wash heads interchangeable
- Up to 40 wash protocols programmable
- Minimal residual volume
- Low well-to-well variation
- On-board automatic self-diagnostic program
- Automatic liquid monitoring system
- Touch screen

MW-12

Microplate Washer

Specifications

Wash programs	Up to 40
Wash cycles	Up to 9
Dispensing volume	50 up to 450 μ l in 1 μ l increment
Dispensing accuracy	<5% at 300 μ l
Liquid flow rate and Aspiration strength	Programmable
Residual volume per well	<2 μ l for U, V bottom plates; and <3 μ l for flat bottom plates
Soak time	Up to 99 seconds
Manifold options	1 x8, 1x 12
Standard bottle set	1 x 3.5L (Wash), 1 x 3.5L (Waste)
Input	Touch screen
Power supply	AC 220V \pm 10%, 50/60Hz AC 110V \pm 10%, 50/60Hz
Temperature	10 $^{\circ}$ C ~40 $^{\circ}$ C
Humidity	15%~80%
Dimension	380mm(H)x350mm(W)x190mm(D)
Weight	7.5Kg



MINDRAY

Headquarters: Mindray Building, Keji 12th Road South, High-tech Industrial Park,
Nanshan, Shenzhen 518057, P. R. China
Tel: +86 755 26582492, 26582888 Fax: +86 755 26582500, 26582501
E-mail: intl-market@mindray.com.cn Website: www.mindray.com.cn



DISTRIBUTOR: