

Medical Cylinder Specifications



Part No.	Service Pressure	Diameter	Length	Empty Weight	Oxygen	Water	Thread Size
	(psi / bar)	(in / mm)	(in / mm)	(lbs / kgs)	(cu ft / liters)	(lbs / liters)	
M150	2216 / 153	8.00 / 203.2	36.2 / 919	39.5 / 17.9	150.0 / 4248	64.9 / 29.4	1.125-12 UNF-2.5
MM	2216 / 153	8.00 / 203.2	35.7 / 907	39.0 / 17.7	122.0 / 3455	47.0 / 21.3	1.125-12 UNF-2.5
M90	2216 / 153	7.25 / 184.2	32.4 / 823	30.3 / 13.7	90.0 / 2549	34.5 / 13.7	1.125-12 UNF-2.5
M60	2216 / 153	7.25 / 184.2	23.1 / 586	22.3 / 10.1	60.0 / 1699	23.6 / 10.7	1.125-12 UNF-2.5
ME	2015 / 139	4.38 / 111.3	24.9 / 632	7.4 / 3.4	24.0 / 680	10.2 / 4.6	.750-16 UNF-2.5
M22	2216 / 153	5.25 / 133.4	16.3 / 414	8.1 / 3.7	22.0 / 623	8.7 / 4.0	.750-16 UNF-2.5
MD	2015 / 139	4.38 / 111.3	16.5 / 419	5.1 / 2.3	15.0 / 425	6.4 / 2.9	.750-16 UNF-2.5
M9	2015 / 139	4.38 / 111.3	10.7 / 272	3.6 / 1.6	9.0 / 255	3.8 / 1.7	.750-16 UNF-2.5
ML6	2015 / 139	4.38 / 111.3	7.6 / 193	2.7 / 1.2	6.0 / 170	2.5 / 1.2	.750-16 UNF-2.5
M6	2216 / 153	3.21 / 81.5	11.6 / 294	2.2 / 1.0	6.0 / 170	2.3 / 1.0	.750-16 UNF-2.5
M4	2216 / 153	3.21 / 81.5	8.4 / 213	1.6 / .7	4.0 / 113	1.6 / .7	.750-16 UNF-2.5
M2	2216 / 153	2.50 / 63.5	5.6 / 143	.70 / .3	1.5 / 42	.6 / .3	.750-16 UNF-2.5

MATERIAL: Every cylinder is produced from high strength aluminum alloy 6061-T6.

FINISH: Standard finish is brushed body with green shoulder and clear coat of heat sensitive powder paint.

VALVE PROTECTION: The MM, M90 and M60 are available with either a valve protector carrying handle or collar and cylinder cap.