

# macro Pipette Controller

## Ideal handling

The unique valve system makes bellows compression easy. With one small sensitive lever, filling and delivery are easily controlled. Precise meniscus adjustment is effortless. A hydrophobic membrane filter protects the macro pipette controller from liquid penetration.



## Economical

The silicone adapter on the macro pipette controller fits the entire range of volumetric and graduated pipettes, both glass and plastic, from 0.1 to 200 ml. There is no need for multiple instruments. The macro pipette controller is fully autoclavable at 121 °C.

## Award winning design

The combination of easy-to-use controls, light weight (106 g) and relaxed operation makes the macro pipette controller ideal for repetitive pipetting even for inexperienced user.

Liquid Handling



Volumetric and measuring pipettes can be found on pages 130-138.

## Ordering Data



## macro Pipette Controller

### Items supplied:

Each pipette controller is supplied with spare membrane filter 3 µm.

| Color   | Cat. No. |
|---------|----------|
| gray    | 261 00   |
| green   | 261 51   |
| blue    | 261 52   |
| magenta | 261 54   |

### Spare parts for macro Pipette Controller

| Description                                     | Pack of | Cat. No. |
|---|---------|----------|
| Membrane filter 3 µm (PP, PTFE), non-sterile    | 1       | 260 52   |
| Membrane filter 3 µm (PP, PTFE), non-sterile    | 10      | 260 56   |
| Adapter (silicone), length 44 mm                | 1       | 261 46   |
| Adapter support (PP), gray, length 49 mm        | 1       | 261 48   |
| Valve system (PP, PTFE, silicone)               | 1       | 261 28   |
| Suction bellows (silicone) with screw ring (PP) | 1       | 260 37   |