



## T 18 ULTRA-TURRAX®

An excellent dispersing instrument at a remarkable price! Volume range: 1 - 1.500 ml (H<sub>2</sub>O). An extended speed range allows to work at high circumferential speeds.

- Electronic speed control
- Electronic temperature control
- Electronic overload protection
- Quick release button for dispersing element
- Dispersing elements not included with delivery

### Accessories (Page):

Dispersing elements (62),  
 Stands (106): R 1825, R 1826, R 1827,  
 R 182 Boss head clamp (108),  
 DZM control.o Revolution counter (111)

Motor rating	
input / output	300 / 160 W
Volume range (H <sub>2</sub> O)	1 - 1.500 ml
Max. viscosity	5.000 mPas
Speed range	6.000 - 24.000 rpm
Speed adjustment	stepless
Speed display	scale (1 - 6)
Noise without dispersing element	78 dB (A)
Overload protection	yes
Diameter / length of extension arm	13 mm / 165 mm
Dimensions (W x D x H)	78 x 78 x 220 mm
Weight	1,2 kg
Permissible ambient temperature	5 - 40 °C
Permissible relative humidity	80 %
Protection class acc. to DIN EN 60529	IP 20

Ident. No.

**L004638**

230 V 50/60 Hz

Ident. No.

**L004637**

115 V 50/60 Hz