

### MSH basic

Magnetic stirrer with stainless steel heating plate

Stirring quantity (H <sub>2</sub> O)	5 L
Temperature range	RT - 350 °C
Speed range	0 - 2,000 rpm
Heat output	400 W
Heating plate surface	Ø 125 mm
Dimensions (W x D x H)	160 x 210 x 105 mm
Weight	2.3 kg
Protection class acc. to DIN EN 60529	IP21

**MSH basic**  
Id-Nr. 3131200



### MST mini

Magnetic stirrer without heating

Stirring quantity (H <sub>2</sub> O)	800 ml
Motor rating input / output	4 / 0.5 W
Speed range	0 - 1,500 rpm
Set-up surface	115 x 115 mm
Max. load	2 kg
Dimensions (W x D x H)	115 x 130 x 40 mm
Weight	0.23 kg
Protection class acc. to DIN EN 60529	IP42



**MST mini**  
Id-Nr. 3287000

### BIG SQUID

Magnetic stirrer without heating

- With very good chemical resistance provided by glass top
- Electronically controlled motor with infinitely variable speed

Stirring quantity (H <sub>2</sub> O)	1.5 L
Motor rating input / output	2 / 1 W
Speed range	0 - 1,500 rpm
Set-up surface	Ø 160 mm
Max. load	5 kg
Dimensions (W x D x H)	180 x 180 x 48 mm
Weight	1 kg
Protection class acc. to DIN EN 60529	IP54



**BIG SQUID**  
Id-Nr. 3286000

### Topolino

Magnetic mini-stirrer

Extremely convenient magnetic mini-stirrer for mixing quantities up to 250ml

- \* Durable, brushless motor
- \* Infinitely variable speed range
- \* High magnetic adhesion

Stirring quantity (H <sub>2</sub> O)	max. 250 ml
Motor rating input / output	1.1 / 0.8 W
Speed range	300 - 1,800 rpm
Max. magnetic bar (L x Ø)	40 x 6 mm
Set-up plate material / dimensions	PP / 81 x 70 mm (oval)
Dimensions (W x D x H)	100 x 130 x 55 mm
Weight	300 g
Permissible ambient temperature / relative humidity	5 - 40°C / 80%
Protection class acc. to DIN EN 60529	IP21



**new**



**Topolino**  
Id-Nr. 3377000

### yellow MAG MS 10 / MS 7 / MS 4

New magnetic stirrers without heating

- Ceramic top plate
- Excellent resistance to chemicals
- Microprocessor technology: guarantees maximum speed control accuracy



**yellow MAG MS 10**  
Id-No. 3644500

**yellow MAG MS 7**  
Id-No. 3644300

**yellow MAG MS 4**  
Id-No. 3644100

	yellow MAG MS 10	yellow MAG MS 7	yellow MAG MS 4
Stirring quantity (H <sub>2</sub> O)	15 L	10 L	5 L
Speed range	100 - 1.500 min <sup>-1</sup>	100 - 1.500 min <sup>-1</sup>	100 - 1.500 min <sup>-1</sup>
Set-up surface (L x W)	260 x 260 mm	180 x 180 mm	100 x 100 mm
Dimensions (W x D x H)	300 x 415 x 105 mm	220 x 330 x 105 mm	150 x 260 x 105 mm
Weight	approx. 6 kg	approx. 5 kg	approx. 3 kg
Protection class acc. to DIN EN 60529	IP 21	IP 21	IP 21
<b>Id-No.</b>	<b>3644500</b>	<b>3644300</b>	<b>3644100</b>

Connect With Us

