

Ordering information



Transferpette® S, Digital adjustable

Items supplied:

Each Transferpette® S Digital adjustable pipette is conformity certified and supplied with performance certificate and rack mount.

Capacity µl	Description	A* ≤ ± % µl	CV* ≤ % µl	Cat. No.
0.1 - 1	D-1	2 0.02	1.2 0.012	7047 68
0.5 - 10	D-10	1 0.1	0.5 0.05	7047 70
2 - 20	D-20**	0.8 0.16	0.4 0.08	7047 72
10 - 100	D-100	0.6 0.6	0.2 0.2	7047 74
20 - 200	D-200**	0.6 1.2	0.2 0.4	7047 78
100 - 1000	D-1000	0.6 6	0.2 2	7047 80
500 - 5000	D-5000	0.6 30	0.2 10	7047 82
1000 - 10000	D-10000	0.6 60	0.2 20	7047 84

Transferpette® S, Fixed volume

Items supplied:

Each Transferpette® S Fixed volume pipette is conformity certified and supplied with performance certificate and rack mount.

Capacity µl	Description	A* ≤ ± % µl	CV* ≤ % µl	Cat. No.
10	F-10	1 0.1	0.5 0.5	7047 08
20	F-20**	0.8 0.16	0.4 0.08	7047 16
25	F-25	0.8 0.2	0.4 0.1	7047 20
50	F-50	0.8 0.4	0.4 0.2	7047 28
100	F-100	0.6 0.6	0.2 0.2	7047 38
200	F-200**	0.6 1.2	0.2 0.4	7047 44
500	F-500	0.6 3	0.2 1	7047 54
1000	F-1000	0.6 6	0.2 2	7047 62

* Calibrated to deliver (TD, Ex). Error limits according to the nominal capacity (= maximum volume) indicated on the instrument, obtained with instrument and distilled water at equilibrium with ambient temperature at 20 °C, and with smooth operation. A = Accuracy, CV = Coefficient of variation.

** For use only with 2-200 µl pipette tips

