

Characteristics



Structure	White or Stainless steel 18/10 int.+ext.
Insulation thickness	50 (polyur. mm)
Doors number	1
Door type	Glass
Shelves nr.	suggested 4
Refrigeration type	Ventilated
Refrigerant type	R404A
Temperature range	+2° +15°
Temperature control/adjustment	ECT-F Control® : with Hi/Low Temp. alarm, door ajar, ON/OFF w/password
Defrosting type	Auto
Voltage	230V/1/50Hz
Castors	standard fitted
Capacity (LT)	200
Internal lighting	standard fitted
Width (cm)	52
Depth (cm)	57
Height (cm)	176
Net weight (Kg)	88
Equipment in accordance with	Directives 2006/42/CE, 2006/95/CE, 2004/108/CE and following modifications

Automatic condensate water evaporation.
Internal cabinet with shelves/drawers interchangeable

Accessories

- Additional open wire shelf realized in sheet steel plastic coated
- Drawer realized in aluminium
- Safety key locking
- Inner electrical sockets
- Cable port
- Humidity measuring sensor
- PT100 probe
- WEB LIGHT SERVER (Ethernet + GSM)
- GSM Communicator CF2008 module
- Frequency 60Hz
- Voltage 115V
- DMLP Digital Monitor (Alarm System)®
- Accessories for DMLP Digital Monitor® :
 - DMLP Printer (Graphic Temp. Printer)
 - DMLP Remote panel
 - Ext. terminal board for RS485/dry contacts
 - DMLP PT100 Extension module + nr.1 PT100 + 4-20mA output

