



**PM-600Vet** | PM-600 I NIBP/PR  
PM-600 II NIBP/SpO<sub>2</sub>/PR  
PM-600 III SpO<sub>2</sub>/PR  
NIBP/SpO<sub>2</sub> VETERINARY MONITOR

- Compact and portable, allowing for uninterrupted monitoring with built-in battery
- Display of NIBP, SpO<sub>2</sub> and Pulse rate via LED with high brightness
- 3 configurations selectable
- Manual/auto/continuous measurement of NIBP
- Automatic audible and visual alarms
- Storage of NIBP data up to 650 groups or SpO<sub>2</sub> data up to 10 hours
- External printer available

# PM-600Vet

PM-600 I NIBP/PR  
PM-600 II NIBP/SpO<sub>2</sub>/PR  
PM-600 III SpO<sub>2</sub>/PR

## NIBP/SpO<sub>2</sub> VETERINARY MONITOR



### Technical Specifications

#### Safety

IEC6060-1 approved, CE marking according to MDD93/42/EEC

#### Dimension and Weight

Dimension: 6cm (H) x 18cm (W) x 22cm (D)

Weight: 1.8 kg

#### Operation Environment

Power requirements: AC 100 ~ 250V, 50/60Hz

Temperature

Working: 0 ~ 40°C

Transport and Storage: -20 ~ 60°C

Humidity

Working: 30 ~ 85%

Transport and Storage: 30 ~ 95% (No Congealment)

Altitude

Working: -500 to 4,600m (-1,600 to 15,000ft)

Transport and Storage: -500 to 13,100m (-1,600 to 43,000ft)

#### Performance Specifications

Displays

Type: LED

Parameters: SpO<sub>2</sub>, NIBP, pulse rate;

Status: BAT, AC, mmHg, Kpa, Adult, NEO, CUFF

Battery: Two Rechargeable 1.3 A/Hr 6V

Lead- Acid battery, lasting for more  
Than 2 hours

#### NIBP

Method: Oscillometric  
Mode: Manual/Automatic/Continuous  
Measurement unit: mmHg/Kpa selectable  
Automatic measurement interval: 1, 2, 3, 5, 10, 30, 45, 60, 90, 120, 180, 240, 480 minutes  
Measurement range: 15-255mmHg  
Alarm: Systolic, Diastolic, Mean  
Alarm Range: 15~255mmHg  
Resolution: 1mmHg

#### SpO<sub>2</sub>

Measurement range: 0~100%  
Resolution: ±1%  
Accuracy: 2% (70%~100%), 0~69% unspecified  
Alarm range: 0~100%

#### Pulse Rate

Range: 0~254bpm  
Resolution: 1bpm  
Accuracy: ±1bpm  
Alarm range: 0~254bpm

#### Review

Trend review: Storage and review of NIBP data up to 900 groups or SpO<sub>2</sub> data up to 22 hours

#### Option

External thermal printer

Dimension: 21cm x 10cm x 10cm  
Weight: 1Kg  
Record Width: 48mm  
Recording types: real-time recording  
Parameter alarm recording: 250 sets of NIBP and SpO<sub>2</sub> data

Interface: RS232 Serial interface  
Power: AC 100 ~ 250V, 50/60Hz



### Mindray Co., Ltd.

Headquarters: Mindray Building, Keji 12th Road South, High-tech Industrial Park, Nanshan, Shenzhen 518057, P. R. China

Tel: +86 755 26582484, 26582888 Fax: +86 755 26582500, 26582501

E-mail: vet-market@mindray.com.cn Website: www.mindray.com.cn



North America Office:  
4885 Kingsway, Suite 311 Burnaby, B.C. V5H4T2, Canada  
Toll free: 800-656-9088 Tel: +1 604-451-1199 Fax: +1 604-451-1189