

# ROTANTA 46 RC/46 RSC



The ROTANTA 46 RC and 46 RSC are refrigerated floorstanding centrifuges. Moveable on castors, they can be conveniently pushed under the bench. Information on their comprehensive range of accessories on request.



## TECHNOLOGY

### ROTANTA 46 RC

### ROTANTA 46 RSC

Underbench centrifuge, without rotor	cooled			
Power supply <sup>1)</sup>	208 – 240 V 1 ~	110 – 127 V 1 ~	208 – 240 V 1 ~	110 – 127 V 1 ~
Frequency	50 – 60 Hz	60 Hz	50 – 60 Hz	60 Hz
Consumption	2,500 VA	2,000 VA	2,500 VA	2,000 VA
Emission	EN 55011 group 1, class B, EN 61000-3-3	FCC class B	EN 55011 group 1, class B, EN 61000-3-3	FCC class B
Immunity	EN 61000-6-2	-	EN 61000-6-2	-
Max. capacity	4 x 750 ml			
Max. RPM (speed)	15,000 min <sup>-1</sup>			
Max. RCF	24,400			
Running time	1 sec – 99 resp. 999 („S“) min : 59 sec, ∞ continuous run, short cycle mode (impulse key – N control panel only)			
Dimensions (HxWxD)	630 x 580 x 685 mm			
Weight	approx. 113 kg	approx. 119 kg	approx. 113 kg	approx. 119 kg
<b>Refrigeration</b>				
Temperature control, infinitely variable	from -20 to +40 °C			
Cat. No.	4812	4812-01	4813	4813-01