

Electric Models

Wisconsin Aluminum Foundry was first in the field to develop an immersion-type pressure sterilizer for physicians' offices, hospitals and laboratories. The electric ALL-AMERICAN® Sterilizer is a complete, self-contained unit with an immersion heating element, automatic thermostatic control, automatic release valve, and pilot light. It connects to any outlet, is ready for use instantly, and ensures complete, efficient sterilization.

- Available in 120V or 240V
- Operational on 50Hz or 60Hz
- Calrod immersion heating element
- 3-wire grounded cord and plug for safety
- Optional support bases elevate electric sterilizers above table or counter surface to prevent heat damage
- UL approved
- One year warranty
- Units include aluminum inner container with rack
- Interior stainless steel support stand
- Made in U.S.A.



Note: Optional support base elevates electric sterilizers to prevent intense heat from damaging counter top or work surface.

25X Features:

- Our most economical electrical unit
- Fenwal thermostat control and pilot light
- 120 or 240 volt operation
- 1050 watt heating element
- 25 qt/24 liter capacity

50X Features:

- 1650 watt heating element for faster start-up, 50% faster than 25X
- 36% greater heating capability compared to 25X
- More accurate TPI thermocouple, snapswitch and pilot light
- 60 minute mechanical bell timer
- 120 or 240 volt operation
- 25 qt/24 liter capacity

75X Features:

- 64% greater capacity compared to 25X
- 120 or 240 volt operation
- 1650 watt heating element for faster operation
- More accurate TPI thermocouple, snapswitch and pilot light
- 60 minute mechanical bell timer
- Extra large 41 qt/39 liter capacity

SPECIFICATIONS



Model 25X (25 qt/24 liter)

Model 25X-120: 120 Volt, 50/60 Hz 1050 watts/8.75 amps

Model 25X-240: 240 Volt, 50/60 Hz 1050 watts/4.38 amps

Gross Capacity 25 qt / 24 liter

Overall Height 16³/₄" / 42.5cm

Bottom Height 12¹/₄" / 31.2cm

Inside Diameter 12⁵/₈" / 32.1cm

Unit Weight 26 lbs. / 11.8kg.

Inner Container No. 2156

Height 8¹/₂" / 21.6cm

Diameter 11¹/₈" / 28.3cm

Circumference 35⁷/₈" / 91.1cm

Capacity 14.5 qt / 13.7 liter

Volume 835in³ / 13,688cm³

Carton Dimensions 21" x 17¹/₂" x 18¹/₂"

53.4cm x 44.5cm x 47cm

Shipping Weight 31 lb. / 14kg.

Unit Pack: 1 Cube: 3.93

Optional No. 2180 Support Base

Height 2" / 5cm high

Outside Diameter 12³/₄" / 32.4cm

Inside Diameter 12³/₈" / 31.4cm

Elevates Sterilizer Above Surface 1³/₈" / 3.5cm

Model 50X (25 qt/24 liter)

Model 50X-120: 120 Volt, 50/60 Hz 1650 watts/13.75 amps

Model 50X-240: 240 Volt, 50/60 Hz 1650 watts/6.88 amps

Gross Capacity 25 qt / 24 liter

Overall Height 16³/₄" / 42.5cm

Bottom Height 12¹/₄" / 31.2cm

Inside Diameter 12⁵/₈" / 32.1cm

Unit Weight 29 lbs. / 13.2kg.

Inner Container No. 2156

Height 8¹/₂" / 21.6cm

Diameter 11¹/₈" / 28.3cm

Circumference 35⁷/₈" / 91.1cm

Capacity 14.5 qt / 13.7 liter

Volume 835in³ / 13,688cm³

Carton Dimensions 21" x 17¹/₂" x 18¹/₂"

53.4cm x 44.5cm x 47cm

Shipping Weight 34 lb./15.4kg.

Unit Pack: 1 Cube: 3.93

Optional No. 2180 Support Base

Height 2" / 5cm high

Outside Diameter 12³/₄" / 32.4cm

Inside Diameter 12³/₈" / 31.4cm

Elevates Sterilizer Above Surface 1³/₈" / 3.5cm

Model 75X (41 qt/39 liter)

Model 75X-120: 120 Volt, 50/60 Hz 1650 watts/13.75 amps

Model 75X-240: 240 Volt, 50/60 Hz 1650 watts/6.88 amps

Gross Capacity 41 qt / 39 liter

Overall Height 19" / 48.3cm

Bottom Height 14¹/₄" / 36.2cm

Inside Diameter 15¹/₄" / 38.7cm

Unit Weight 45 lbs. / 20.4kg.

Inner Container No. 4156

Height 10¹/₄" / 26cm

Diameter 14" / 35.6cm

Circumference 44¹/₂" / 113cm

Capacity 27.3 qt / 25.8 liter

Volume 1578in³ / 25,856cm³

Carton Dimensions 24" x 24" x 21"

61cm x 61cm x 53.3cm

Shipping Weight 51 lb. / 23.1kg.

Unit Pack: 1 Cube: 7

Optional No. 4180 Support Base

Height 3" / 7.6cm high

Outside Diameter 16¹/₄" / 41.3cm

Inside Diameter 15" / 38.1cm

Elevates Sterilizer Above Surface 2¹/₄" / 5.7cm