

BATTERY SUCTION ASPIRATORS

- 28240 SUPER TOBI BATTERY - plastic case - 16 l/min.
- 28190 SUPER VEGA BATTERY - plastic case - 30 l/min.
- 28213 TROLLEY FOR SUPER VEGA


With incorporated rechargeable batteries. It can operate at 12 V power supply at rechargeable batteries and, thanks to an electronic system, at 230 V while recharging batteries. Autonomy: approx 45-50 minutes. Recharging time: 120-150 minutes. Max suction: -75 bar
Suction power: 16 air litres/min
It has unbreakable 1,000 ml standard bottle (2,000 ml optional) autoclavable at 120°C with safety float control valve to prevent overflow.

TECHNICAL SPECIFICATIONS SUPER TOBI / SUPER VEGA

Operating Voltage: 230 V AC - 12 V DC
Size: 370 x 220 x 210 mm (28240)
350 x 210 x 180 mm (28243 / 28190)
Weight: 5.5 kg (28240) 4.9 kg (28243 / 28190)
Max suction -0.75 bar (563 mm/Hg)
Suction power: 16 air litres/min (28240 / 28243)
30 air litres/min (28190)
Norms: IEC 601-1 - Class II Type B. Made in Italy



28240



Cable to recharge battery from power supply

Cable to recharge batteries from car

30 l/min.



CE 0123

28206



Disposable suction liner, Autoclavable jar, Aspirator, Carrying bag

28259 28258



1 l jar with overflow safety valve

30 l/min.

28190

STANDARD ACCESSORIES

- Bottle 1 l - autoclavable at 120°C
- Silicone tubing set
- Suction catheter
- Anti-bacteria filter
- Cable to recharge batteries from power supply
- Cable to recharge batteries from car
- User manual (English, French, Spanish, German, Italian)

- 28241 MINI ASPEED BATTERY - metal case - 18 l/min
 - 28206 MINI ASPEED BATTERY PRO - metal case - 30 l/min
- Portable medical device for professional surgical aspiration.
- It can operate at 12 V (car..) power supply, rechargeable batteries or directly by mains supply.
 - Its two cylinders electro-compressor ensures high performances and long life.
 - Up to 45 min. of autonomy with fully charged battery.
 - With 99% antibacterial hydrophobic filter
 - Equipped with autoclavable jar with safety valve, disposable suction liner and carrying case.
 - 25850 SILICONE TUBE 6X12 mm - minimum 30m
 - 28254 ADAPTOR FOR CATHETER
 - 28255 HYDROPHOBIC 99% BACTERIAL FILTER
 - 28258 AUTOCLAVABLE JAR 1000m (with cover)
 - 28259 DISPOSABLE SUCTION LINER

Disposable suction liner inside autoclavable jar

TECHNICAL SPECIFICATIONS MINI ASPEED

Operating Voltage: 100-240 V 50/60 Hz AC - 14 V DC 4.28 A
Size: 370 x 100 x 240 mm Weight: 5.8 kg (include kit)
Max suction - 0.80 bar (650 mm/Hg)
Suction power: 30 air litres/min. (28206) 18 air l/min. (28241)
Sound level: 65 db
Norms: MDD 93/42/ECC (class IIa - annex IX)
IEC 60601-1, UNI ENISO 10079-1
Made in Italy

STANDARD ACCESSORIES

- Autoclavable jar 1000 cc
- Anti-bacteria hydrophobic filter with safety valve
- Multivoltage battery charger
- Silicone tubing set Ø 6x12 mm
- Cigarette lighter power cord.
- Disposable suction liner
- Shoulder carrying bag
- Sterile cannula
- User manual (English and Italian)



28258 + 28259

SUPERVEGA SUCTION ASPIRATOR ON TROLLEY

CE 0123

Vacuum indicator
Max suction:
600 mm Hg - 0.80 bar

Adjustable suction knob

Fixed height 75 cm

2 l jar

28191

- 28191 SUPER VEGA on trolley - suction 2x2 l jar
 - 28192 SUPER VEGA on trolley - suction 2x2 l jar with footswitch
- Continuously adjustable vacuum, with indicator. Silicone connection tube. 2 jars 2 litres, made of sterilizable polycarbonate (autoclavable at 120°C). Working time: 120 min ON, 60 min. OFF. Suction power: 40 air litres/min. Steel painted frame, fitted with 5 star base. Norms CEI 62-5 (IEC 601-1) - Class II - Type B
- 28239 HYDROPHOBIC 99% BACTERIAL FILTER

TECHNICAL SPECIFICATIONS

Size: 32 x 30 x 90 h cm Weight 6.2 kg
Operating voltage: 230 V - 50 Hz.; other on request
Power consumption: 110 VA
Maximum suction: - 0.80 bar (600 mm Hg)
Flow: 40 air litres/minute
Temporary use: 120 on - 60 off
Norms CEI 62-5 (IEC 601-1) - CEI 93/42 EEC
User manual (English, French, German, Italian, Spanish)
Made in Italy



Supervega on trolley with disposable jars 28272/3 and 28274/5. See page 85