

Modalities > Portable Electrotherapy

NEW PRIMERA™ TENS/NMES (OTC). Loaded with 14 preset Programs (8 TENS and 6 NMES) along with the exclusive HAN TENS waveform—a unique dense-and-disperse (DD) mode of stimulation, in which low frequency stimulation (2 Hz) sequences with high frequency stimulation (15 or 70 Hz) to accelerate the release of opiates to effectively manage pain and reduce muscle spasm. Includes PRIMERA Unit, carrying case, battery, leadwires, Dura-Stick electrodes, back support belt and user's manual.

5686-94 PRIMERA Package

5687-25 Leadwires (pair)

Specifications

Channels	Dual	Pulse Rate	TENS: 2-150 HZ NMES: 12-35 Hz
Modes	Continuous, Burst, Modulation, HAN, NMES	Pulse Width	TENS: 175-250 s NMES: 200-250 s
Output	0-80 mA	Waveforms	Asymmetrical bi-phasic rectangle

chattanooga® Deluxe Intellect® Tens Unit. Includes 2" x 2" sample electrodes, lead wires and a cover for the top controls.

5541-15 \$186.85

Deluxe Intellect® Tens Unit Specifications

Channels	Dual	Pulse Width	60-250 µs
Output	0-80mA	Timer	30, 60, or continuous mode
Pulse Rate	2-150 HZ	Waveforms	Modified square wave with zero net direct current (DC) components

BioMed® 2000 XL TENS Device. Includes carrying case, lead wires, 9V battery, four reusable electrodes and instruction manual.

2997

2996-01 Replacement Lead Wires (pair)

BioMed® 2000 XL TENS Specifications

Channels	Dual	Pulse Rate	2-150 Hz
Waveforms	Asymmetrical biphasic square	Pulse Width	50-250 s
Output	0-98 mA	Voltage	0-40V
Modes	Continuous, Burst, Width Modulation		

BioStim® M7 TENS. Includes carrying case, lead wires, two AA batteries, four reusable electrodes and instruction manual.

9692-22

2996-01 Replacement Lead Wires (pair)

5638-61 BioStim® 2" Square Replacement Electrodes. 40/pk

BioStim M7 TENS Specifications

Channels	Dual	Output	0-98 mA
Frequency	1-200Hz	Pulse Rate	1- 200 Hz
Intensity	0-98 mA	Pulse Width	10-250 s
Modes	Continuous, Width modulation, Rate modulation, Rate and Width modulation, SD1, SD2, cycled burst	Voltage	49V
		Waveforms	Asymmetrical rectangular biphasic
		Dimensions	3.25"L x 2.25"W x 2"H

Impulse TENS D5. Includes carry case, lead wires, 2 AA batteries, four reusable electrodes and instruction manual.

9692-20

Impulse TENS D5 Specifications

Channels	Dual	Pulse Rate	1-120Hz
Modes	Constant, Width modulation, Rate modulation and 2 different types of Burst	Pulse Width	25-250 s
Output	0-100 mA	Waveforms	Symmetrical biphasic square
		Dimensions	4.2"L x 2.9"W x 1.4"H



Connect With Us

