

IMS Anesthesia Equipment Line



Previous



Next

Table of
Contents

Product
Index

Search

Home

Contact
Us




Previous



Next


NEW Pneumatic Fittings and CO₂ Chambers



BS4 34-0451



BS4 34-0452



BS4 34-0454



BS4 34-0453

NEW Pneumatic Fittings

Spares and / or upgrades can be made to existing anesthetic systems by use of pneumatic quick release fittings.

Catalog No.	\$	Model	Product
BS4 34-0451		8.19.10	1/4" UNC Thread, Female Quick Release Fitting for Use on Chambers etc.
BS4 34-0452		8.19.11	Male Quick Release Fitting with Push in Fitting for 6mm OD Pneumatic Tubing
BS4 34-0453		8.19.12	Coiled 6mm OD Tubing
BS4 34-0454		8.19.13	6mm OD Pneumatic Tubing, Natural Color, sold per meter

NEW CO₂ Chambers with Dump Door



An added option for CO₂ Chambers is to have a dump door fitted. This enables CO₂ to be cleared from the chamber without having to tip up the chamber and waiting, therefore saving time and effort.

The Chamber is easily and quickly opened and closed, and locked in place by means of a

centrally placed knob. The side opening is below the false floor. Three chambers sizes are available.

Specifications

Dimensions, H x W x D:

Large Chamber	305 x 305 x 455 mm (12 x 12 x 17.9 in)
Medium Chamber	200 x 200 x 200 mm (7.9 x 7.9 x 7.9 in)
Small Chamber	150 x 100 x 255 mm (5.9 x 3.9 x 10 in)

Catalog No.	\$	Model	Product
BS4 34-0434		8.17.0	CO ₂ Chamber with Dump Door, Large
BS4 34-0435		8.17.1	CO ₂ Chamber with Dump Door, Medium
BS4 34-0436		8.17.2	CO ₂ Chamber with Dump Door, Small



BS4 34-0429



BS4 34-0430



BS4 34-0431

NEW Anesthetic/ CO₂ Chambers

These chambers have a 6mm wall thickness and can be ordered in either white or clear Perspex. The lid is 10mm thick clear Perspex and has a foam sealing strip.

Inside, the chamber has a false perforated aluminium floor resting on nylon supports. Brass straight fittings are supplied as standard. The inlet is below the grill floor and outlet at top of opposite end.

Three different sized chambers area available.

Product BS4 34-0452 Quick Release Inlet (male fitting) is available separately. This fitting is for use with coiled pneumatic fitting systems.

Specifications

Dimensions, H x W x D:

Large Chamber	315 x 305 x 455 mm (12.4 x 12 x 17.9 in)
Medium Chamber	210 x 200 x 305 mm (8.3 x 7.9 x 12 in)
Small Chamber	160 x 100 x 255 mm (6.3 x 3.9 x 10 in)

Catalog No.	\$	Model	Product
BS4 34-0429		8.14.0	Anesthetic/CO ₂ Chamber, Large
BS4 34-0430		8.14.1	Anesthetic/CO ₂ Chamber, Medium
BS4 34-0431		8.14.2	Anesthetic/CO ₂ Chamber, Small
BS4 72-1080		—	Silicone Tubing 3/16" ID, 1/4" OD, 25 ft
BS4 72-3043		—	Male Endcap with Barb for 3/16" to 1/4" ID Tubing



Connect With Us

