

Stirring Hot Plates

MULTIPLE STIRRING HOT PLATES

PMC

PMC 526C



A WIDE RANGE OF MULTIPLE STIRRING CONFIGURATIONS!

- Aluminum, ceramic, or porcelain heating surfaces
- Several stirring options

PRODUCT SPECIFICATIONS

Model #	Heating Surface Inches (cm)		Heating Surface Material	Overall Dimensions Inches (cm)			Shipping Weight Lb. (kg)
	W	D		W	H	D	
524A	4 (10.1)	4 (10.1)	Aluminum	10.5 (26.7)	6.5 (16.5)	15 (38.1)	35 (15.9)
524C	4 (10.1)	4 (10.1)	Ceramic	10.5 (26.7)	6.5 (16.5)	15 (38.1)	35 (15.9)
525A	10 (25.4)	10 (25.4)	Aluminum	10.5 (26.7)	6.5 (16.5)	15 (38.1)	33 (15)
525P	10 (25.4)	10 (25.4)	Porcelain	10.5 (26.7)	6.5 (16.5)	15 (38.1)	33 (15)
525C	10 (25.4)	10 (25.4)	Ceramic	10.5 (26.7)	6.5 (16.5)	15 (38.1)	33 (15)
526A	4 (10.1)	4 (10.1)	Aluminum	28 (71.1)	5.6 (14.2)	8 (20.3)	45 (20.4)
526C	4 (10.1)	4 (10.1)	Ceramic	28 (71.1)	5.6 (14.2)	8 (20.3)	45 (20.4)
529A	10 (25.4)	10 (25.4)	Aluminum	10.5 (26.7)	6.5 (16.5)	15 (38.1)	39 (17.7)
529P	10 (25.4)	10 (25.4)	Porcelain	10.5 (26.7)	6.5 (16.5)	15 (38.1)	39 (17.7)
529C	10 (25.4)	10 (25.4)	Ceramic	10.5 (26.7)	6.5 (16.5)	15 (38.1)	39 (17.7)

PRODUCT DESCRIPTION

- Four and six place units have individual tops and controls. Five and nine place units have a single top plate with individual stir controls.
- Designed to stir aqueous and viscous (e.g. glycerine) solutions.
- Solid, white ceramic tops heat up fast, remain flat at maximum temperatures and are resistant to acid and alkali.
- Porcelain-coated stainless steel top plates heat up more slowly, are designed for low temperature applications and are chemically resistant.
- Units are built from durable cast aluminum cases and painted with chemically resistant paint.
- Five and nine place units hold five 800 ml and nine 400 ml beakers, respectively.
- Weight limits: 20 lb. (9.1 kg) on the 10" x 10" models and 10 lb. (4.5 kg) on the 4" x 4" models.
- Not recommended for use with metal vessels.

OPERATION

- Aluminum tops heat up quickly and uniformly. Great for low temperature applications.
- Heat control has a power indicator light to help the operator assess the on/off status of the unit at a glance.
- Percentage input control provides infinite temperature settings.

ORDERING INFORMATION

Model #	Electrical (50/60 Hertz)			Operating Temp Range		Stirring Speed RPM	# of Stirrers	US List Price
	Volts	Amps	Watts	°C	°F			
524A	120	10.4	1252	75 - 400	167 - 752	100 - 1200	4*	
524C	120	10.4	1252	100 - 500	212 - 932	100 - 1200	4*	
525A	120	12.7	1527	75 - 400	167 - 752	100 - 1200	5	
525P	120	12.7	1527	50 - 350	122 - 662	100 - 1200	5	
525C	120	12.7	1527	100 - 400	212 - 752	100 - 1200	5	
526A	120	18.5	2229	75 - 400	167 - 752	100 - 1200	6*	
526C	120	18.5	2229	100 - 500	212 - 932	100 - 1200	6*	
529A	120	13.6	1640	75 - 400	167 - 752	100 - 1200	9	
529P	120	13.6	1640	50 - 350	122 - 662	100 - 1200	9	
529C	120	13.6	1640	100 - 400	212 - 752	100 - 1200	9	

*Individual Stirrer Tops
230V models available, add "-2" to above model number

48 Hour or Sooner Express Shipping Guaranteed!*



*see inside front cover for details

Barnstead/Thermolyne

155

800-553-0039 or 319-556-2241