

CS48

SURFACE WIDTH: 120cm - 48"

- ISO Class 4 Air Quality (ISO 14644-1) for maximum protection
- Dual configuration of the working surface: flat or recessed
- Weights only 185kg (407lbs): 20% lighter than others on the market; easy to transport around the facility
- Ergonomic design and sturdy construction
- Energy saving blowers (ECM Technology)
- Low energy LED strip provides uniform light on the work surface
- A dimmer controls light intensity to accepted levels for albino strands
- Injection molded polysulfone airflow grille around the work surface reduces noise and turbulence generated by inside air flow
- Acoustic comfort. Low levels of noise and vibration
- Overall energy savings and reduced heat load emissions
- High cleanability
- Reduced turbulence and noise inside working surface



ARIA CS48 IS INDEPENDENTLY CERTIFIED (UL/CSA) AND COMPLIANT WITH CE REQUIREMENTS.

QUALITY MATERIALS ARE IN CONFORMITY TO GUARANTEE THE STRICTEST SAFETY STANDARDS.



Dual Access. ISO Class 4 Air Quality.
Innovative Flat or Recessed Working Surface

- **EFFECTIVE BARRIER:** PREVENTS CROSS-CONTAMINATION AND ALLERGEN EXPOSURE
- **FLEXIBILITY:** DUAL CONFIGURATION WORKING SURFACE FITS FROM THE SMALLEST TO THE LARGEST CAGES
 - **LIGHTER.** 20% LESS WEIGHT THAN OTHER MODELS ON THE MARKET

OVERALL DIMENSIONS (WxDxH)	WORKING AREA DIMENSIONS (WxDxH)	WEIGHT
1414 x 790 x 1954 - 2278 mm 55" 5/8 x 31" 3/8 x 76" 7/8 - 89" 5/8	1120 x 610 x 640 mm (flat mode) - 690 mm (recessed mode) 44" 1/8 x 24" x 25" 2/8 (flat mode) - 27" 1/8 (recessed mode)	185 kg 408 lbs



Magnifier kit
and
retractable cable

