Lab biosafety waste generator

Lab biosafety waste generator

Lab biosafety waste generator is dry sterilizing Waste Disposing System with biosafety guarding function. It' s mainly used for disposing the solid wastes caused by a little high-risk infectious or pathologic inspection in hospitals or labs, especially including the excision body of human and animals; microbiologic incubation, PCR experiment wastes; needle and syringe of injection, etc.

Pressure-proof: AC1500V can`t be punctured in one minute
Grounding resistance: ≤0.1Ω
Power supply: AC220V±22V
Power frequency: 50Hz
Dimension: 360×260×230/ 325×300×440mm
Process temperature: above 170℃
Process time: above 170℃,maintain over 1.5 hours
Process capacity : 0.6L/3L

Laminar Flow Cabinets

Horizontal Laminar Flow Cabinets

needle and syringe of injection, etc.

Model	External Size (W*D*H)	Internal Size (W*D*H)	Type
BBS-DDS	1060×800×1690 mm	980×500×600 mm	One operator
BBS-SDS	1460×800×1690 mm	1400×500×600 mm	Two operators
BBS-1300HGS	1300×825×2000 mm	1200×500×570 mm	Two operators

Protection: sample
Side walls: tempered glass
Worktable: stainless steel
Dust: ≥0.5μm ≤3.5 granule/L
Clean Rate: >99.995% at 0.3μm
Airflow Speed: 0.3-0.5m/s
Noise: <60dB(A level)
Vibration: XYZ direction<5μm
Power supply: 220V 50HZ
Power consumption: 600W
Option: water tap, gas tap

BBS-SDS BBS-1300HGS

سوماتكو
SOMATCO
www.somatco.com