

## Automatic burettes, Pellet pattern, without intermediate stopcock

### SILBERBRAND, class B

DURAN®. DIN EN ISO 385. Calibrated to deliver (TD, Ex). Schellbach stripe. With needle-valve stopcock with PTFE spindle. Automatic zeroing. Total height incl. 2000 ml bottle (soda-lime glass) approx. 1m. Pack of 1.

Capacity ml	Subdivision ml	Error limit ± ml	Description	Cat. No.
10	0.02	0.03	with bottle	219 14
25	0.05	0.05	with bottle	219 17
50	0.1	0.08	with bottle	219 18
10	0.02	0.03	without bottle	219 11
25	0.05	0.05	without bottle	219 12
50	0.1	0.08	without bottle	219 13



## Automatic burettes, Pellet pattern, with intermediate stopcock

### SILBERBRAND, amber glass

Borosilicate glass 5.4.

25 ml: Error limits according to class B, DIN EN ISO 385.

50 ml: DIN EN ISO 385, class B.

Calibrated to deliver (TD, Ex). Available with titration stopcock with PTFE key (PTFE key in intermediate stopcock) or STJ glass stopcock (glass key in intermediate stopcock).

Automatic zeroing. Intermediate stopcock 4 NS/19 for recirculating residual liquid.

Total height approx. 1m incl. 2000 ml bottle (soda-lime glass). Pack of 1.

#### Titration and intermediate stopcock with PTFE key

Capacity ml	Subdivision ml	Error limit ± ml	Description	Cat. No.
25*	0.1	0.08	with bottle	223 32
50	0.1	0.10	with bottle	223 34
25*	0.1	0.08	without bottle	223 36
50	0.1	0.10	without bottle	223 38

\* reduced distance between subdivision marks

#### Titration and intermediate stopcock with glass key

Capacity ml	Subdivision ml	Error limit ± ml	Description	Cat. No.
25*	0.1	0.08	with bottle	223 22
50	0.1	0.10	with bottle	223 24
25*	0.1	0.08	without bottle	223 26
50	0.1	0.10	without bottle	223 28

\* reduced distance between subdivision marks

