

The Modular Burette Concept!

The Compact Burette from BRAND.

- with PTFE stopcock
- fast to dismantle and easy to clean
- simple repair – all individual components replaceable!

Compact Burettes

BLAUBRAND®, class AS, conformity certified

DURAN®, removable PTFE stopcock. DIN EN ISO 385. Calibrated to deliver (TD, Ex).
Items supplied: Burette tube with Schellbach stripe; Stopcock with precision tip.
Incl. one batch certificate. Pack of 1.

Capacity ml	Subdivision ml	Error limit ± ml	Length mm	Cat. No.
10	0.02	0.02	795	139 13
25	0.05	0.03	800	139 16
50	0.1	0.05	800	139 18

Compact Burettes

SILBERBRAND

AR-Glas®, removable PTFE stopcock. Error limits according to class B, DIN EN ISO 385.
Calibrated to deliver (TD, Ex). Items supplied: Burette tube with Schellbach stripe;
Stopcock with precision tip. Pack of 1.

Capacity ml	Subdivision ml	Error limit ± ml	Length mm	Cat. No.
10*	0.05	0.05	445	139 03
25*	0.1	0.08	510	139 06
50*	0.1	0.10	710	139 08

* reduced distance between subdivision marks

Compact Burettes, amber glass

SILBERBRAND

Borosilicate glass 5.4, removable PTFE stopcock.
25 ml: Error limit according to class B, DIN EN ISO 385.
50 ml: DIN EN ISO 385, class B.
Calibrated to deliver (TD, Ex).
Items supplied: Burette tube with white graduation; Stopcock with precision tip. Pack of 1.

Capacity ml	Subdivision ml	Error limit ± ml	Length mm	Cat. No.
25*	0.1	0.08	520	139 26
50	0.1	0.10	790	139 28

* reduced distance between subdivision marks

Connect With Us

