

Burettes acc. to Mohr

Marienfeld volumetric measuring instruments are manufactured with utmost care in a production which is certified according to DIN EN ISO 9001.

Burettes are calibrated "EX" (to deliver). The imprinted volume corresponds to the delivered quantity of liquid

They are available in class B (short-line graduated), class AS (fast delivery, circular graduation at main points) and class AS conformity certified. Conformity (acc. to DIN 12 600) means compliance with the German Calibration Regulations and the relevant standards. By imprinting the mark of conformity "H" we certify that a measuring device complies with these conditions. On request, conformity-certified instruments are available with individual certificate at extra charge. A batch certificate is included in each packing unit.

Marienfeld burettes are also available with Schellbach stripe. This stripe at the back of the instrument facilitates reading precisely the meniscus of a liquid.

Burettes acc. to Mohr, DIN 12 700. borosilicate glass 3.3, straight stopcock, blue graduated, in cartons of 2 pieces, clear glass

class B

glass plug PTFE-plug

Cat. No.	Cat. No.	capacity	tolerance
24 020 01	24 021 01	10:0.02 ml	± 0.05 ml
24 020 11	24 021 11	25:0.05 ml	± 0.05 ml
24 020 21	24 021 21	25:0.1 ml	± 0.05 ml
24 020 31	24 021 31	50:0.1 ml	± 0.1 ml
24 020 41	24 021 41	100:0.2 ml	

class AS

glass plug PTFE plug

Cat. No.	Cat. No.	capacity	tolerance
24 220 01	24 221 01	10:0.02 ml	± 0.02 ml
24 220 11	24 221 11	25:0.05 ml	± 0.03 ml
24 220 21	24 221 21	25:0.1 ml	± 0.05 ml
24 220 31	24 221 31	50:0.1 ml	± 0.05 ml
24 220 41	24 221 41	100:0.2 ml	

class AS conformity certified, with batch certificate

glass plug

Cat. No.	capacity	tolerance
24 320 01	10:0.02 ml	± 0.02 ml
24 320 11	25:0.05 ml	± 0.03 ml
24 320 21	25:0.1 ml	± 0.05 ml
24 320 31	50:0.1 ml	± 0.05 ml
24 320 41	100:0.2 ml	



Burettes acc. to Mohr, DIN 12 700, borosilicate glass 3.3, straight stopcock, blue graduation, class B, in cartons of 2 pcs., with Schellbach stripe

glass plug	PTFE plug		
Cat. No.	Cat. No.	capacity	tolerance
24 030 01	24 031 01	10:0.02 ml	± 0.05 ml
24 030 11	24 031 11	25:0.05 ml	± 0.05 ml
24 030 21	24 031 21	25:0.1 ml	± 0.05 ml
24 030 31	24 031 31	50:0.1 ml	± 0.1 ml
24 030 41	24 031 41	100:0.2 ml	

Burettes acc. Mohr, DIN 12 700, borosilicate glass 3.3, straight stopcock, white graduation, class B, in cartons of 2 pcs., amber glass

glass plug	PTFE plug		
Cat. No.	Cat. No.	capacity	tolerance
24 060 02	24 061 02	10:0.02 ml	± 0.05 ml
24 060 12	24 061 12	25:0.05 ml	± 0.05 ml
24 060 22	24 061 22	25:0.1 ml	± 0.05 ml
24 060 32	24 061 32	50:0.1 ml	± 0.1 ml
24 060 42	24 061 42	100:0.2 ml	



Connect With Us

