

EMOTECA TWIN 1500 ECT-F TOUCH



Characteristics

Temperature Range	+4 °C
Capacity	1355 lt (47,87 cu ft) MORE INFO
Blood bags capacity (450 ml)	672
External Dimensions (W x D x H)	cm 144 x 82 x 205 MORE INFO
Structure and Insulation	sanitized pre-coated steel with bacteriostatic activity, white colour- in/out (rust- corrosion-proof material), or stainless steel 18/10 AISI 304 inside and sanitized pre-coated steel white colour- outside; insulation polyurethane thickness 70 mm
Feet	n.4 adjustable feet
Door	Nr 2 glass doors with triple glass panels
Electric Digital Key Lock	Electric Digital Key Lock MORE INFO
Light	Led type with adjustable brightness
Internal equipment	nr.14 extractible aluminum drawers mounted on telescopic slides MORE INFO
Controller	ECT-F TOUCH + DMLP TOUCH DIGITAL MONITOR MORE INFO
Alarms	Acoustic and Visual for temperature deviations, power failure and faults, with automatic recording even in case the electricity is off
Safety Thermostat	

Blood-bank refrigerator and plasma-freezer : medical device blood bank refrigerator

Data and Event recording	10 years on SD card; 1 year on Flash-memory
Temperature Graph	A customizable real time graphic always visible from the home page.
Connectivity	USB-SD-SIM port with frontal access ; external board for Dry Contact and Serial ports RS485 and RJ45
Refrigeration Type	Forced-air, ventilated
Compressors	Nr.2 MORE INFO
Defrost	Automatic with automatic evaporation of the condensate water
Probe for product simulation	

Technical data

Details	MORE INFO
In accordance with	93/42/CE - class IIa regulation, and following modifications
Package	Strong Cardboard on wooden pallet MORE INFO
note	DIN 58371 conformity

Accessories

Blind Door

Castors with brakes

Extractible Aluminum Drawer with partitions

Plexiglas front for drawers

Wire basket in stainless steel H mm 148

S/Steel Rack cm 14 x 50 x 15 H (max nr.3 each shelf)

GSM Module [MORE INFO](#)

Wi-fi Module [MORE INFO](#)

White coated sheet shelf

Connect With Us

