

EMOTECA 700 ECT-F TOUCH



go to ECT-F version

Characteristics

Temperature Range	+4 °C
Capacity	620 lt (21,91 cu ft) MORE INFO
Blood bags capacity (450 ml)	336
External Dimensions (W x D x H)	cm 72 x 82,5 x 205 MORE INFO
Structure and Insulation	sanitized pre-coated steel with bacteriostatic activity, white colour- in/out (rust- corrosion-proof material), or stainless steel 18/10 AISI 304 inside and sanitized pre-coated steel white colour- outside; insulation polyurethane thickness 60 mm
Door	Nr 1 glass door with triple glass panels
Electric Digital Key Lock	MORE INFO
Height adjustable Feet	
Light	Led type with adjustable brightness
Internal equipment	nr.7 extractible aluminum drawers mounted on telescopic slides MORE INFO
Controller	ECT-F TOUCH + DMLP TOUCH DIGITAL MONITOR MORE INFO
Alarms	Acoustic and Visual for temperature deviations, power failure and faults, with automatic recording even in case the electricity is off
Safety Thermostat	
Data and Event recording	10 years on SD card; 1 year on Flash-memory
Temperature Graph	A customizable real time graphic always visible from the home page.
Connectivity	USB-SD-SIM port with frontal access ; external board for Dry Contact and Serial ports RS485 and RJ45
Refrigeration Type	Forced-air, ventilated
Defrost	Automatic with automatic evaporation of the condensate water
Probe for product simulation	

Technical data

Details	MORE INFO
In accordance with	93/42/CE - class IIa regulation, and following modifications
Package	Strong Cardboard on wooden pallet MORE INFO
note	<ul style="list-style-type: none">• DIN 58371 conformity• Available also in TWIN version (double compressor)

Accessories

Blind Door

Castors with brakes

Extractible Aluminum Drawer with partitions

Plexiglas front for drawers

Wire basket in stainless steel H mm 148

S/Steel Rack cm 14 x 50 x 15 H (max nr.3 each shelf)

GSM Module [MORE INFO](#)

Wi-fi Module [MORE INFO](#)

White coated sheet shelf

Cable port mm 35 with cap

Cable port mm 15

Humidity Sensor

PT100 probe (free contacts)

Voltage stabilizer

4-20mA converter module [MORE INFO](#)

60 Hz Frequency

115 V

Wooden crate Package



Connect With Us

