NEW Gleamer[®] Exam Lights



Next

able of



Product Index

Table of

Contents

- Search
- WWW Home
- Contact Us

- 4,166 footcandles (45,000 Lux) Nearly 35% brighter!
- 3,700°K color temperature (natural coloring)
- 35 W halogen bulb; 4,000 hr life
- Easy bulb replacement without tools
- Cool housing temperature and cool light beam; light can be in continuous use for hours without causing discomfort to physician or patient
- Convenient positioning with ergonomic positioning ridges
- Floorstand includes unique space-saving base (casters included)
- High-quality, space-saving 4-caster base safe and flexible portable movement with locking feature in 2 of 4 casters
- UL 60601-1/60601-2-41 Certified
- Made in the USA

The new patent pending Gleamer® is designed to the most demanding specifications: high intensity, cool operation, compact design, and value. With 4,166 footcandles of intensity, 3,700°K color temperature, and a (combination) 16 inch sturdy gooseneck and optional 15 inch extension arm, Gleamer® offers extensive reach, maximum convenience, and superior flexibility where top performance, reliability, and low cost are required.

For rugged construction, the most stringent regulatory requirement and cool operation, the Gleamer® is the task light of choice. Even with the Gleamer's compact design and high illumination bulb source, its unique venting system and energy-absorbing heat exchanger assures both a cool beam and housing.

The Gleamer's advanced styling, high intensity, and superb quality is unmatched by any other light in its category. Put a Gleam in your eye and see the first 35 watt task light with UL 2601 listing... you'll select the Gleamer® for your all-purpose light.

Order # Product

erder #	1104400
PY2 72-3839	Gleamer® with Floor Stand, 115 VAC, 60 Hz
PY2 72-3840	Gleamer® with Floor Stand, 220 VAC, 50 Hz
PY2 72-3841	Gleamer® with Floor Stand, 230 VAC, 50 Hz
PY2 72-3842	Gleamer [®] with Floor Stand, 240 VAC, 50 Hz
PY2 72-3843	Gleamer® with Extension Arm and Universal Wall Mount, 115 VAC, 60 Hz
PY2 72-3844	Gleamer $^{\odot}$ with Extension Arm and Universal Wall Mount, 220 VAC, 50 Hz
PY2 72-3845	Gleamer $^{\otimes}$ with Extension Arm and Universal Wall Mount, 230 VAC, 50 Hz
PY2 72-3846	Gleamer $^{\otimes}$ with Extension Arm and Universal Wall Mount, 240 VAC, 50 Hz
PY2 72-3847	Gleamer® with Universal Walll Mount, 115 VAC, 60 Hz
PY2 72-3848	Gleamer® with Universal Wall Mount, 220 VAC, 50 Hz
PY2 72-3849	Gleamer® with Universal Wall Mount, 230 VAC, 50 Hz
PY2 72-3850	Gleamer® with Universal Wall Mount, 240 VAC, 50 Hz
PY2 72-3851	Replacement Bulb for Gleamer®, 35 Watt, pkg. of 4



