



Cold in a perfect combination of Design,  
Quality and Professionalism for the Medical field.

## FREEZER 700



### Characteristics

Structure	White or Stainless steel 18/10 int.+ext.
Insulation thickness	60 (polyur. mm)
Doors number	1
Door type	Fully Insulated
Shelves nr.	suggested 3
Refrigeration type	Ventilated
Refrigerant type	R404A
Temperature range	-10° -25°
Temperature control/adjustment	ECT-F Control® : with Hi/Low Temp. alarm, door ajar, ON/OFF w/password
Defrosting type	Auto
Voltage	230V/1/50Hz
Capacity (LT)	700
Internal lighting	standard fitted
Width (cm)	72
Depth (cm)	80
Height (cm)	205
Net weight (kg)	150
Equipment in accordance with	Directives 98/37/CE, 2006/95/CE, 2004/108/CE, 93/42/CE and following modifications
Internal cabinet with shelves/drawers interchangeable	

## Accessories

Additional open wire shelf realized in sheet steel plastic coated  
Drawer realized in aluminium  
Safety key locking  
Kit of castors with brakes  
PT100 sensor  
WEB LIGHT SERVER (Rete Ethernet + GSM)  
GSM Communicator CF2008 module

Interchange Rack System for Shelves/Baskets  
Internal steel wire basket  
Automatic water evaporation tray  
Frequency 60Hz  
Voltage 115V  
DMLP Digital Monitor (Alarm System)®  
Accessories for DMLP Digital Monitor® :  
- DMLP Printer (Graphic Temp. Printer)  
- DMLP Remote panel  
- Ext. terminal board for RS485/dry contacts  
-DMLP PT100 Extension module + nr.1 PT100 + 4-20mA output



Connect With Us

