

Connect With Us



## 净化工作台 Purifying Worktable



水平单向流系列  
Horizontal one-way flow series



垂直单向流系列  
Vertical one-way flow series

### 概述:

本设备为医疗卫生、制药、化学试验、电子、国防、精密仪器、仪表等领域提供无菌、无尘、洁净环境的局部净化空间。

### Summary:

Widely used in medicine, pharmacy, laboratories, electronics, national defence, precision instruments, meters to get nonmicroorganisms, non-dust and clean conditions.

### 产品特点:

- ※ 垂直流形为工作闭合台面, 单向流形为开放式台面,
- ※ 先进的可变风量送风系统和轻触式开关,
- ※ 可任意调节的预过滤进风量;
- ※ 不锈钢台面, 钢化玻璃侧挡板;
- ※ 超薄型过滤器。

### Characteristics:

- ※ Vertical one-way flow purifying worktable—vertical flow, work closed table surface
- ※ Horizontal one-way flow purifying worktable—horizontal flow, open table surface
- ※ Advanced variable flow quantity blast system and touch switch
- ※ Flow adjusted discretionarily
- ※ Table surface is made of stainless-steel and side board is made of toughened glass
- ※ Super thin filter

### 技术参数 Specifications

型号 Model	水平单向流 Horizontal one-way flow			垂直单向流 Vertical one-way flow		
	HRSJ-1D	HRSJ-2D	HRCJ-1D	HRCJ-1S	HRCJ-2D	HRCJ-2S
洁净等级 Cleanliness	100级 @ $\geq 0.5\mu\text{m}$ (美联邦 209E)					
平均风速 Average wind speed	0.3~0.6m/s (可调) Adjustable					
噪声 Noise	$< 62\text{dB(A)}$					
振动与半峰值 Vibration and semi-peak value	$\leq 3\mu\text{m}$			$\leq 4\mu\text{m}$		
照度 Illuminance	$> 300\text{LX}$					
荧光灯 / 紫外灯规格及数量 Daylight & u.v.lamp	18W × ① 20W × ①	30W × ① 30W × ①		18W × ① 20W × ①	30W × ① 30W × ①	18W × ① 20W × ②
最大功耗 Maximum power	0.4kW	0.8kW		0.4kW		0.8kW
电源电压 Voltage	220V 50Hz					
高效过滤器规格数量 Specification and quantity of (HEPA) <sup>5</sup>	760 × 610 × 50 × ①	610 × 610 × 50 × ②		820 × 600 × 50 × ①		610 × 610 × 50 × ②
工作区尺寸 LxWxH(mm) Size of working room	660 × 650 × 570	1120 × 650 × 570	880 × 680 × 570	880 × 700 × 520	1310 × 680 × 520	1310 × 700 × 520
外形尺寸 LxWxH(mm) Outer Size	840 × 825 × 1430	1300 × 825 × 1430	1040 × 770 × 1730	1040 × 790 × 1730	1490 × 770 × 1760	1490 × 790 × 1760
适用人数 Operator	1	2	1	2	2	2