

## **Calipers**

Use these calipers for fast, reliable measurements. Calipers feature beveled jaws for measuring threads. Order caliper accessories, connecting cables, and replacement batteries separately below. Each caliper includes a storage case.





## **Specifications & Ordering Information**

Key letter	Catalog number	Description	Range	Resolution	Accuracy	Price
/ernier ca	aliper	·			· · ·	
А	<u>KH-09921-21</u>	Measure inside, outside, depth; beveled edges for measuring screws; stainless steel (SS) construction with satin chrome finish	0 to 6"/ 0 to 150 mm	0.001"/ 0.05 mm	±0.001"/ ±0.05 mm	
Dial calip	ers					
В	<u>KH-97100-00</u>	Measure inside, outside, depth; adjustable dial; fiberglass/nylon construction for corrosive samples; disposable	0 to 6"	0.01", 1⁄64"	±0.01", ±1/64"	
	KH-97100-10		0 to 150 mm	0.1 mm	±0.1 mm	
С	KH-09924-06	Tough shockproof design; measure inside, outside, depth; beveled edges measure screws; solid SS construction	0 to 6"	0.001"	±0.001"	
	KH-09924-08		0 to 12"	0.001"	±0.001"	
Digital ca	lipers with LCD					
D	<u>KH-97105-00</u>	Low-cost caliper measures inside, outside, depth, step; adjustable zero; friction thumb roller; fiberglass/super polyamide construction	0 to 6"/ 0 to 150 mm	0.001"/ 0.1 mm	±0.001"/ ±0.1 mm	
	KH-97152-08	Measure inside, outside, depth, step; direct inch/metric conversion; patented ceramic capacitive sensor	0 to 6"/0 to 150 mm	0.0005"/	±0.001"/±0.02 mm	
	KH-97152-12		0 to 12"/0 to 300 mm	0.01 mm	±0.0015"/±0.04 mm	
	<u>KH-09923-18</u> *	RS-232 output; measure inside, outside, depth, step; direct inch/ metric conversion, thumb roller, high contrast LCD; 3-year warranty	0 to 6"/ 0 to 150 mm	0.0005"/ 0.01 mm	±0.001"/ ±0.03 mm	
G	<u>KH-09923-20</u> *	RS-232 output; measure inside, outside, depth, step, direct inch/ metric conversion; thumb roller; 3-year warranty	0 to 6"/ 0 to 150 mm	0.001"/ 0.05 mm	±0.001"/ ±0.02 mm	
н	<u>KH-97152-00</u> *	IP65 moisture-resistant; RS-232 output; measure inside, outside, depth, step; direct inch/metric conversion; thumb roller; SS construction	0 to 6"/ 0 to 150 mm	0.0005"/ 0.01 mm	±0.001"/ ±0.02 mm	
	<u>KH-97152-10</u>	Large scale measure inside, outside, depth, step; direct inch/metric conversion	0 to 24"/ 0 to 600 mm	0.0005"/ 0.01 mm	±0.001"/ ±0.03 mm	

\*These calipers feature RS-232 output. Order RS-232 cable below.

Electronic Caliper and Data Acquisition Kit contains electronic caliper 09923-18 ("F") in a shophardened case, and an interface/ data acquisition



kit which includes RS-232 cable, cable adapter, and PC software.

KH-09923-38 Electronic caliper and data acquisition kit

## Accessories

KH-97150-10 Data collection software for calipers with RS-232 output. For Windows®, 3½" disk

KH-97152-50 RS-232 cable for use with calipers 09923-18, -20 and 97152-00. Includes a 6-ft (1.8 m) cable, 9-pin connector and demo software

KH-97155-00 Centerline gauge for 6" calipers. Gauge has 60° conical point for measuring center-to-edge distances from a hole. Measures 0.375" (0.953 cm) dia x 2.2" (5.6 cm) L. Hardened steel

## KH-97155-04 Caliper accessory kit

for challenging applications. Allows inside, outside, step, and groove measurements. Kit includes clamps; four sets of screws; ball, flat, point, and spline contact points; and Allen wrench in a plastic case

KH-09923-71 Replacement battery, type SR44 for models 97105-00 and 09923-20

KH-97152-60 Replacement battery, type CR2032 for model 97152-00

Connect With Us

