

LABOR 2T 400 ECT-F



Characteristics

Temperature Range	+2 / +15 °C ; -10 / -24 °C
Capacity	170 + 160 lt (6,01 + 5,66 cu ft) Gross capacity 170 + 181 lt (6,01 + 6,39 cu ft)
External Dimensions (W x D x H)	cm 60 x 63 x 201,5 Internal Dimensions (W x D x H) cm 50 x 49,6 x 68,5 / 50 x 49,6 x 73; Weight Kg 123
Structure and Insulation	sanitized pre-coated steel with bacteriostatic activity, white colour-in/out (rust- corrosion-proof material); insulation polyurethane thickness 70 mm in the back, 50 in the sides
Door	Nr 2 blind doors pre-coated steel white colour, with ergonomic handle in aluminum
Rollers	rollers
Light	Led type
Suggested internal fittings	nr.4 shelves (2+2) Interchangeable system that allows to mix: <ul style="list-style-type: none"> • open wire shelves supported by plastic clips, adjustable in height (dim.cm.47,5 x 46); • extractible aluminum drawers mounted on telescopic slides (dim. cm.12 x 40 x 7,5 for 3 compartments)
Controller	Nr.02 ECT-F ECT-F CONTROL with LCD Display with no.4 soft touch pads, with a 0,1 °C resolution. Customizable menu, available in 5 languages. Acoustic and visual signals for: <ul style="list-style-type: none"> • Open door • High Temperature • Low temperature • Power failure (when the energy returns, only in event of High Temperature) • Dirty Condenser The last 12 events are always available from the display. Clear and precise information of the status of the machine are indicated on the display, as well as all the failures. A password, if enabled, identifies two distinct levels of access to the controller (User and Service), and protects the modification of functional parameters, such as switch on, switch off and set-point of the equipment. The display can be customized, enabling you instant verification of all the main settings for a quick resolution of any problems (Doctor View). Special functions Stop-On-Door, Second Cooling and Advanced Defrosting allow the complete management of the refrigeration cycle, reducing temperature peaks and consumption.
Alarms	Acoustic and Visual for temperature deviations and failures
Data and Event recording	last 12 events available from display
Refrigeration Type	Forced-air, ventilated
Defrost	Automatic with automatic evaporation of the condensate water

Technical data

Technical Data	<ul style="list-style-type: none"> • Refrigerant gas type: R404A CFC free • Mains Voltage 230V/1/50Hz • Power consumption 24H: 7,8 kW/24H • Instant power consumption: 0,3+0,6 kW (1,8+4 A) • Noise level < 53 dB
-----------------------	---

- Ambient Temperature: +16/+32 °C; humidity 60%
- Connector: Schuko

In accordance with	2006/42/CE, 2006/95/CE, 2004/108/CE, 93/42/CE and following modifications
Package	Strong Cardboard on wooden pallet Dim. cm.66x71x215; Kg.132 • Wooden crate on wooden pallet available: dim. cm.76x77x215; Kg.165

Accessories

Key Lock

Glass Door for fridge compt.

Additional Shelf

Extractible Aluminum Drawer with partitions

Plexiglas front for drawers

Dry Contact

Cable port mm 35 with cap

Cable port mm 15

Humidity Sensor

PT100 probe (free contacts)

60 Hz Frequency

115 V

Wooden crate Package



Connect With Us

