

Refrigerator LABOR 400 ECT-F TOUCH

[← BACK](#)

go to ECT-F version

Characteristics

Temperature Range	+2 / +15 °C
Capacity	347 lt (12,26 cu ft) MORE INFO
External Dimensions (W x D x H)	cm 60 x 65,5 x 195,5 MORE INFO
Structure and Insulation	sanitized pre-coated steel with bacteriostatic activity, white colour- in/out (rust- corrosion-proof material), or stainless steel 18/10 AISI 304 inside and sanitized pre-coated steel white colour- outside; insulation polyurethane thickness 70 mm in the back, 50 in the sides
Door	Nr 1 blind door pre-coated steel white colour, with ergonomic handle in aluminum
Rollers	rollers
Light	Led type with adjustable brightness
Suggested internal fittings	nr.4 shelves MORE INFO
Controller	ECT-F TOUCH MORE INFO
Alarms	Acoustic and Visual for temperature deviations and failures, with automatic recording
Safety Thermostat	
Data and Event recording	10 years on SD card; last year on Flash-memory
Temperature Graph	A customizable real time graphic always visible from the home page.
Connectivity	USB-SD-SIM port with frontal access ; Dry Contact; Serial ports RS485 and RJ45
Refrigeration Type	Forced-air, ventilated
Defrost	Automatic with automatic evaporation of the condensate water

Technical data

Details	MORE INFO
In accordance with	2006/42/CE, 2006/95/CE, 2004/108/CE, 93/42/CE and following modifications
Package	Strong Cardboard on wooden pallet MORE INFO

Accessories

Electric Digital Key Lock [MORE INFO](#)

Glass Door

Additional Shelf

Extractible Aluminum Drawer with partitions

Plexiglas front for drawers

Sliding wire stainless steel drawer H mm 62

Stainless steel wire rack cm 14 x42 x 15 H (max 3 each shelf)

Back-up Batteries [MORE INFO](#)

External Terminal Board for RS485/Ethernet/Dry Contact

Dmlp Digital Monitor Touch [MORE INFO](#)

GSM Module [MORE INFO](#)

Wi-fi Module [MORE INFO](#)

DIN 58345 conformity [MORE INFO](#)

Internal Socket

Internal Sockets (n.2 with On/OFF)

Cable port mm 35 with cap

Cable port mm 15

Humidity Sensor

PT100 probe (free contacts)

Voltage stabilizer

4-20mA converter module [MORE INFO](#)

60 Hz Frequency

115 V

Wooden crate Package



Connect With Us

