

Characteristics



Structure	Stainless steel int. + ext.
Insulation thickness	60 (polyur. mm)
Doors number	1
Door type	Glass
Shelves nr.	suggested 3
Refrigeration type	Ventilated
Refrigerant type	R404A
Temperature range	+2° +15°
Temperature control/adjustment	ECT-F Control® : with Hi/Low Temp. alarm, door ajar, ON/OFF w/password
Defrosting type	Auto
Voltage	230V/1/50Hz
Capacity (LT)	600
Internal lighting	standard fitted
Width (cm)	72
Depth (cm)	73
Height (cm)	205
Net weight (Kg)	126
Equipment in accordance with	Directives 2006/42/CE, 2006/95/CE, 2004/108/CE and following modifications
Internal cabinet with shelves/drawers interchangeable	

Accessories

- Additional open wire shelf realized in sheet steel plastic coated
- Rack for nr 12 plasma bags (450 ml) Max. nr 3/ shelf
- Drawer realized in aluminium
- Safety key locking
- Kit of castors with brakes
- Inner electrical sockets
- Cable port
- Humidity measuring sensor
- PT100 probe
- WEB LIGHT SERVER (Ethernet + GSM)
- GSM Communicator CF2008 module
- Interchange Rack System for Shelves/Baskets
- Internal steel wire basket
- Automatic water evaporation tray
- Frequency 60Hz
- Voltage 115V
- DMLP Digital Monitor (Alarm System)®
- Accessories for DMLP Digital Monitor® :
 - DMLP Printer (Graphic Temp. Printer)
 - DMLP Remote panel
 - Ext. terminal board for RS485/dry contacts
 - DMLP PT100 Extension module + nr.1 PT100 + 4-20mA output



Connect With Us



At any time, the manufacturer may bring modifications to the model above described, for technical or commercial reasons. The picture does not necessary shows the product in the standard version.