

Oxygen Regulators



The World's Most Compact and Convenient Regulators!

EASY REG OXYGEN REGULATOR

The World's Most Compact and Convenient Oxygen Regulators.



168708D



They're Compact and Lightweight...

The EasyDialReg is only 4.25 in. long and weighs a mere 7.8 oz. as a result of the offset gauge and multi-spring technology. The EasyGaugeReg is only 4.63 in. long and weighs 12 oz. with the contents gauge on the front and the flow gauge on the top.

They're User-Friendly...

Both types of regulators have easily accessible flow adjustment knobs making flow adjustment a cinch.

They're Safety is Built in...

The Easy Reg line of oxygen regulators feature a built-in pressure relief valve as well as a protected contents gauge. The low force Viton yoke seal provides a better tank-to-reg seal.

They're Safe...

The EasyDialReg has passed the ASTM G175 Ignition Sensitivity and Faulty Tolerance Test.

They're Accurate...

Unique design minimizes normal flow variation that occurs as tank pressure drops.

They're Flexible & Versatile...

The ÉasyDialReg comes in two (2) body designs yoke or nut style, and is available in five (5) flow ranges: 31-4000 cc/min, 1/32-4 lpm, .25-8 lpm, .50-15 lpm and .25-25 lpm. The EasyGaugeReg also comes in the two (2) body designs and two (2) flow ranges: 0-8 lpm and 0-15 lpm.

Color Gauge Guard Option

All models of Precision Medical's EasyReg can be ordered with any one of six different color gauge protectors, green being our standard. Different colors may be used to identify and segregate regulators by department. When ordering, please remember to add a dash (-) between the regulator part number and the desired color suffix. (Green gauge guard requires no suffix.) (Ex.: 168708D-Y)







Specifications

| | | CGA Connection | |
|---------------|------------------------------------------------------------------|---------------------|--------------------|
| Flow Range | Position Increments | Yoke Style (870) | Nut Style (540) |
| 0-4000 cc/min | OFF, 31, 62, 125, 250, 500, 750, 1000, 1500, 2000, 3000 and 4000 | 168704DCL | 165404DCL |
| 0-4 lpm | OFF, 1/32, 1/16, 1/8, 1/4, 1/2, 3/4, 1, 1-1/2, 2, 3 and 4 | 168704DL | 165404DL |
| 0-8 lpm | OFF, .25, .50, 1, 1.5, 2, 2.5, 3, 4, 5, 6 and 8 | 168708D | 165408D |
| 0-15 lpm | OFF, .50, 1, 1.5, 2, 3, 4, 5, 6, 8, 10 and 15 | 168715D | 165415D |
| 0-25 lpm | OFF, .25, .50, 1, 2, 3, 4, 6, 8, 10, 15 and 25 | 168725D | 165425D |

Ordering Information

EasyDialReg

| DSDS | DSDR | DSR | NG | 0706 |
|------------------------------------|---------------------------------------------------------|----------------------------------------------------------|-----------------------------|--------------------------------------------------------------------------------|
| | | | | |
| 168715DSDS shown Outlet DISS O2 | 168715DSDR shown Outlet DISS O2 90° pointing down | 168715DSR shown Outlet Hose Barb 90° pointing down | 168708DNG shown No Gauge | 168715DSDS/0706 shown Extension used with DSDS for humidifier bottles |

EasyGaugeReg

| , , , | | | | | |
|-----------|------------------|-----------------|--|--|--|
| Flow Rate | Yoke Style (870) | Nut Style (540) | | | |
| 0.0 lpm | 168708G | 165408G | | | |
| 0-8 lpm | 168708GE | 165408GE | | | |
| 0.15 lpm | 168715G | 165415G | | | |
| 0-15 lpm | 168715GE | 165415GE | | | |

Accessories & Replacement Parts

Yoke Seal

The low force Viton yoke seal provides a better tank-toreg seal. It has a brass outer ring.



Ordering Information

1221-25 Yoke Seal (Pack of 25)

Disposable Tubing Nipple

Fits any Regulator with an Oxygen DISS fitting.



Ordering Information

0120 Yellow 0121 Black 0122 White 0124 Green

T-Handle

The T-Handle and Ring Retainer for the handle are parts for the Precision Medical Piston Regulators.




Ordering Information

502312 Ring, Retaining504156 Handle Assembly, Yoke

Humidifier

The Humidifier is disposable. It has a 350 cc capacity. Features a 2 psi pop-off valve. 50 per Case.





Ordering InformationPM500 Humidifier

Oxygen & Air Diaphragm Regulator Industry Standard • 50 PSI Preset Regulators



870 Preset



540 Preset

These brass diaphragm regulators provide a minimum flow of 240 lpm at a constant pressure of 50 psi with DISS male outlet.

Ordering Information

| Gas | CGA Connection | Style | Part Number |
|-------------|-------------------|-------|-------------|
| Oxygen | 870 | Yoke | 870 |
| | 540 | Nut | 540 |
| Medical Air | 950 | Yoke | 504450 |
| | 346 | Nut | 504448 |

Connect With Us













