

400

- An integral printer with selectable automatic print-intervals. A printout can be obtained every 15, 30, or 60 seconds or at other intervals up to 10 minutes.
- **Screens for Nighttime Desaturation**
 Mode 1: All low saturation events below a pre-set point are recalled for later printout.
 Mode 2: The oximeter recalls the lowest point reached during consecutive two-minute periods for the entire monitoring session.
 Tape printouts include the percentage of time below 90, 80, 70 and 60% saturation.
- Easily changed snap-in paper cartridge.
- Rechargeable battery pack with four-hour battery capacity. The external battery pack can be changed in seconds for continuous monitoring.



Oxygen Saturation and Pulse Rate	Display	Two 3-digit, 7-segment LED 1.5cm (0.6 in) high characters
	Resolution	1% SpO ₂ or 1 beat/minute (BPM)
	Range	SpO ₂ : 0-100% Pulse: 25-250 BPM
	Accuracy	SpO ₂ : 100-70%, ±2% 69-60%, ±3% Less than 60% unspecified Pulse: 25-250 BPM, ±2
Alarms	Saturation and rate	
General	Size	30.0cm L × 14.0cm W × 6.5cm H (12 in L × 5½ in W × 2½ in H)
	Weight	1.36 kilos (3.0 Lbs)
Sensor Compatibility	Uses all Palco Opto-Plethysmographic Sensors	
Power Source	Battery Type	NiCad rechargeable
	Battery Life	4 hours continuous, with 8 hour charge
	A/C Adaptor	120V, 60Hz AC to 18V DC, or 220-240V, 50Hz AC to 18V DC

