



SK-700I Enteral Feeding Pump

Enteral feeding pump is affordable of delivering reliably and safely enteral feeding formulas.





SK-700I Enteral Feeding Pump

Enteral feeding pump is affordable of delivering reliably and safely enteral feeding formulas.

Features

- Continuous or bolus enteral feeding capabilities for nutrition delivery
- Dedicated feeding bag for accurate and reliable nutrition delivery
- Innovative door-less design for easy operation
- Flexible power supply (100-240V, 50/60Hz) and lithium battery
- Feeding rate range (1-400ml/h with increment 1ml/h)
- Audible and visible alarm system
- Wireless data transmission with infusion supervision system (optional)



Connect With Us



Technical Specifications

■ Technical Descriptions

Feeding Rate Range	1 - 400 ml/h (increment 1 ml/h)
Accumulated Feeding Volume	1 - 9999 ml
Volume Limit	1 - 9999 ml (increment 1 ml/h)
Accuracy	± 10%
KVO	1 ml/h
Bolus Rate	400 ml/h

■ Display

Screen	2.7 inch B/W LCD
Information	Rate, Preset Volume, Volume limit, Accumulated feeding volume, Bed No., AC Power indicator, Battery capacity, Battery charge indicator

■ Alarm Type

Air Bubble, Finish, No AC, Low Battery, Battery Empty, Communication abnormal (Error 1), Operating abnormal (Error 2), Handle open (Error 4)

■ Battery

Type	7.4 V, 1600 mAh lithium polymer battery
Life	More than 4 hours' continuous operation @25ml/h flow rate (optional)

■ Environment

Temperature	5 - 40°C for operating; -20 - 50°C for storage
Air Pressure	86 - 106 kPa for operating; 50 - 106 kPa for storage
Humidity	20 % - 80 % for operating; 10 % - 95 % for storage

■ Others

Dimension	120 mm(L) × 140 mm(D) × 195 mm(H)
Weight	About 1.7kg
Power Supply	100 - 240 VAC, 50/60 Hz
Shell Material	ABS plastic
Water proof level	IPX1