

## Freezer SUPERARTIC 700 ECT-F TOUCH



go to ECT-F version

### Characteristics

<b>Temperature Range</b>	-20 / -40 °C
<b>Capacity</b>	544 lt (19,22 cu ft) <a href="#">MORE INFO</a>
<b>External Dimensions (W x D x H)</b>	cm 72 x 86 x 205 <a href="#">MORE INFO</a>
<b>Structure and Insulation</b>	sanitized pre-coated steel with bacteriostatic activity, white colour- in/out (rust- corrosion-proof material), or stainless steel 18/10 AISI 304 inside and sanitized pre-coated steel white colour- outside; insulation polyurethane thickness 60 mm
<b>Feet</b>	n.4 adjustable feet
<b>Door</b>	Nr 1 blind door pre-coated steel white colour, with ergonomic handle in aluminum
<b>Suggested internal fittings</b>	nr.3 shelves <a href="#">MORE INFO</a>
<b>Controller</b>	ECT-F TOUCH <a href="#">MORE INFO</a>
<b>Alarms</b>	Acoustic and Visual for temperature deviations and failures, with automatic recording
<b>Safety Thermostat</b>	
<b>Data and Event recording</b>	10 years on SD card; last year on Flash-memory
<b>Temperature Graph</b>	A customizable real time graphic always visible from the home page.
<b>Connectivity</b>	USB-SD-SIM port with frontal access ; Dry Contact; Serial ports RS485 and RJ45
<b>Refrigeration Type</b>	Forced-air, ventilated
<b>Defrost</b>	Automatic

### Technical data

<b>Technical Data</b>	<a href="#">MORE INFO</a>
<b>In accordance with</b>	2006/42/CE, 2006/95/CE, 2004/108/CE, 93/42/CE and following modifications
<b>Package</b>	Strong Cardboard on wooden pallet <a href="#">MORE INFO</a>

### Accessories

Electric Digital Key Lock [MORE INFO](#)

Castors with brakes

Additional Shelf

Wire basket in stainless steel H mm 148

Sliding wire stainless steel drawer H mm 62

Stainless steel wire rack cm 14 x42 x 15 H (max 3 each shelf)

S/Steel Rack cm 14 x 50 x 15 H (max nr.3 each shelf)

Back-up Batteries [MORE INFO](#)

External Terminal Board for RS485/Ethernet/Dry Contact

Dmlp Digital Monitor Touch [MORE INFO](#)

GSM Module [MORE INFO](#)

Wi-fi Module [MORE INFO](#)

Condensate water evaporation tray

Cable port mm 35 with cap

Cable port mm 15

PT100 probe (free contacts)

Voltage stabilizer

4-20mA converter module [MORE INFO](#)

60 Hz Frequency

115 V

Wooden crate Package

---



Connect With Us

