

Freezer SUPERARTIC 700 ECT-F TOUCH



go to ECT-F version

Characteristics

Temperature Range	-20 / -40 °C
Capacity	544 lt (19,22 cu ft) MORE INFO
External Dimensions (W x D x H)	cm 72 x 86 x 205 MORE INFO
Structure and Insulation	sanitized pre-coated steel with bacteriostatic activity, white colour- in/out (rust- corrosion-proof material), or stainless steel 18/10 AISI 304 inside and sanitized pre-coated steel white colour- outside; insulation polyurethane thickness 60 mm
Feet	n.4 adjustable feet
Door	Nr 1 blind door pre-coated steel white colour, with ergonomic handle in aluminum
Suggested internal fittings	nr.3 shelves MORE INFO
Controller	ECT-F TOUCH MORE INFO
Alarms	Acoustic and Visual for temperature deviations and failures, with automatic recording
Safety Thermostat	
Data and Event recording	10 years on SD card; last year on Flash-memory
Temperature Graph	A customizable real time graphic always visible from the home page.
Connectivity	USB-SD-SIM port with frontal access ; Dry Contact; Serial ports RS485 and RJ45
Refrigeration Type	Forced-air, ventilated
Defrost	Automatic

Technical data

Technical Data	MORE INFO
In accordance with	2006/42/CE, 2006/95/CE, 2004/108/CE, 93/42/CE and following modifications
Package	Strong Cardboard on wooden pallet MORE INFO

Accessories

Electric Digital Key Lock [MORE INFO](#)

Castors with brakes

Additional Shelf

Wire basket in stainless steel H mm 148

Sliding wire stainless steel drawer H mm 62

Stainless steel wire rack cm 14 x42 x 15 H (max 3 each shelf)

S/Steel Rack cm 14 x 50 x 15 H (max nr.3 each shelf)

Back-up Batteries [MORE INFO](#)

External Terminal Board for RS485/Ethernet/Dry Contact

Dmlp Digital Monitor Touch [MORE INFO](#)

GSM Module [MORE INFO](#)

Wi-fi Module [MORE INFO](#)

Condensate water evaporation tray

Cable port mm 35 with cap

Cable port mm 15

PT100 probe (free contacts)

Voltage stabilizer

4-20mA converter module [MORE INFO](#)

60 Hz Frequency

115 V

Wooden crate Package



Connect With Us

