



Spectro UV-2505

UV-VIS Spectrophotometer



Spectro UV-2505 is a low priced traditional analytical device used in conventional laboratories. This spectrophotometer delivers enhanced user-friendliness, precision and accuracy resulting in time and cost savings, as well as unprecedented confidence in test results. Model UV-2505 works in the ultraviolet and visible range of **195-1050 nm** and has a **4nm. Bandwidth!** Model **UV-2505** spectrophotometer offers high performance and reliability, which can be used in various applications. Spectrophotometer Model **UV-2505** can be used extensively for pharmaceutical manufacturing, health, clinical laboratory, biochemistry, petrochemistry, environmental protection, quality control, water management, food processing, agriculture, and for a wide range of businesses and industries. It is equipped with the **RS-232C** interface and port which link the spectrophotometer and the PC using the UV-VIS optional software. Model UV-2505 can be linked to a computer, which is compatible with Windows Platforms, and a printer to display the photometric and spectral data on the PC monitor.

Spectro UV-Vis RS (Model UV-2505) utilizes a new optical system design and is microcomputer controlled. This instrument has soft keys for ease of use and may utilize 13 mm test tube. Model UV-2505 has excellent baseline stability and high resolution. It consists of a light source (Tungsten Halogen and Deuterium lamp), monochromator, Silicon photodiode, logarithmic amplifier, digital volt meter, D.C. stabilizer, and microprocessor. This new generation instrument is equipped with a microprocessor to automatically adjust 100 % T and Zero ABS, Factor, and Concentration. Spectro UV-VIS 2505 operates with a single beam system and 1200 line grating mirror. Model UV-2505 has a four digit display for automatic calculation and direct readout of (T)ransmittance, (A)bsorption, and (C)oncentration.

This Spectro can be used by itself or linked to a PC. Can use a multiple cell holder to test cells from 10-100mm (optional)

Labomed, Inc. is certified by ISO 9001-2000, has CE Conformity and is FDA Licensed.

Features

This instrument is the realization of a long history of specialized research, design, and manufacture. It is simple in construction and high in performance. The multiple cell holder is one of the unique features of the Spectro UV-VIS 2505. It is able to test, record and print four sample results immediately by built in interface RS 232C. The Spectro may save the reagents and samples by using the optional semi-micro cuvette of 1.5 ml or less to reduce waste. This unit was constructed with high reliability, durability, ease of operation, and maintenance in mind.

Easy to change light source.
Very competitive price.
Has FDA license.

4 nm bandwidth. **NEW AND IMPROVED!**
Wide continuous wavelength 200-1050nm
Multi-purpose cell holder for long path
(20 - 50mm) rectangular cells

Set of 2 performance testing filters (1 "E filter" for photometric accuracy test and 1 didymium filter for wavelength accuracy test)
Optional Software for Windows 95/98/XP/7
Includes RS232C cable, operator's manual. (Specify: Spectro UV-Vis 2505)

Accessories

Power cable
Software cable
Operation Manual

Technical Specifications

Optical system:	Single beam, diffraction grating	Concentration range:	0-1999
Light Source:	Tungsten Halogen and Deuterium lamps	Direct-read Range	0-1999
Bandwidth:	4nm	Largest Allowable Error (T)	0.5%
Wavelength:	195nm-1050nm	Photometric accuracy:	0.5% T
Largest Allowable Error (Wavelength)	2nm	Monochromator:	1200 lines/grating mirror
Absorbance Range:	0.0000-2.0000	Noise:	100% Noise <0.3% T/3min, 0% Noise <0.2%
Wavelength Accuracy:	<2%	Stability:	bright <0.5%/3 min., dark <0.2%/3 min
Wavelength Reproducibility:	1nm	Transmittance reproducibility:	0.2 % T
Spectral Band Pass:	4nm	Power Supply:	AC85-260V, 50Hz or 60Hz
Stray Light:	<0.3 % T (at 220 nm. 360nm)	Weight:	12 Kg. (26.4 lbs.)
Transmittance Range:	0-100% T	Dimensions:	410mm (L) x 310mm (W) 155mm. (H)
Multi cell holder:	4 cuvettes		16.1" (L) x 12.2" (W) 6.1" (H)



Connect With Us